JANUARY 2002



For

U.S. Environmental Protection Agency Region 2 and U.S. Army Corps of Engineers Kansas City District

TAMS Consultants, Inc.

TI A D	A E OE COMBENIES	Page
TAB	ELE OF CONTENTS	
	Book 1 of 3	
	Book 2 of 3	
	Book 3 of 3	
	List of Acronyms and Abbreviations	XXV
EXE	CUTIVE SUMMARY	Executive Summary-1
INTI	RODUCTION TO THE RESPONSIVENESS SUMMARY	Introduction-1
COM	MMENTS & RESPONSES (BOOK 1 of 3)	
1. I.	EGAL AND POLICY ISSUES	
1.1	ARARs and TBCs	1-1
1.2	Policy Issues.	
	1.2.1 CERCLA Requirements and Issues	
	1.2.2 Applicability of the NAS Report	
1.3	Public/Citizen Participation Process	
1.5	1.3.1 Peer Review Process	
	ACKGROUND AND REMEDIAL INVESTIGATION	
2.1	Sources of PCBs to the Upper Hudson River	
2.2	Validity of the Low Resolution Sediment Coring Report	
2.3	Other Geochemistry Issues	
2.4	Baseline Modeling Assumptions	
	2.4.1 HUDTOX	
	2.4.2 FISHRAND	
	2.4.3 Farley Model	
2.5	PCB Transport to the Lower Hudson River	
2.6	Long-Term Trends in PCB Concentrations	
2.7	Adequacy of RI Data Collection to Support the FS	2-77
3. B.	ASELINE RISK ASSESSMENTS AND PRGS	
3.1	Baseline Human Health Risk Assessment	3-1
	3.1.1 PCB Toxicity	3-1
	3.1.1.1 PCB Toxicity – Cancer	
	3.1.1.2 PCB Toxicity – Non-Cancer	
	3.1.2 Fish Consumption (Rate and Species Mix)	
	3.1.3 Exposed Population	
	3.1.4 Sensitive Populations and Additional Exposure Routes	
3.2	Baseline Ecological Risk Assessment	
	3.2.1 Ecological Toxicity of PCBs	
	3.2.2 Field Studies	3-41

Bool	<u>k 1 of 3</u>	Page
	3.2.3 Ecological Risk Assumptions	3-54
3.3	Preliminary Remediation Goals (PRGs)/Fish Concentration Target	
4.	REMEDIAL ACTION OBJECTIVES AND SELECTION OF TAI	RGET AREAS
4.1	Attainment of RAOs	4-1
4.2	Determination of Target Areas and Volumes	
	4.2.1 PCB Mass vs. Surface Concentration	4-16
	4.2.2 Cohesive vs. Non-Cohesive sediments	4-17
	4.2.3 Minimum Target Area for Dredging (50,000 sq ft minimum	n)4-19
4.3	Use of Mass per Unit Area (MPA) as a Criterion	4-21
4.4	Section-Specific Target Criteria	4-24
4.5	Habitat-Based Targeting	4-28
5. T	TECHNOLOGY EVALUATION AND REMEDIAL ALTERNATIVE	E DEVELOPMENT
5.1	Technology Evaluation	5-1
	5.1.1 Capping/Aquablok TM	5-1
	5.1.2 Treatment/Vitrification	5-2
	5.1.3 Dredging Technologies	5-5
5.2	Remedial Alternative Development	
5.3	Comparison of MNA vs. Active Sediment Remediation	5-17
6. N	MODELING ASSUMPTIONS AND INTERPRETATION	
6.1	Fate and Transport Modeling	
	6.1.1 External PCB Loads to the Model	6-4
	6.1.2 Spatial Resolution of Modeling	6-7
	6.1.3 Post-Remediation Sediment Residuals	6-10
	6.1.4 Resuspension	6-12
6.2	Bioaccumulation Modeling	6-16
6.3	Lower Hudson River Modeling	6-20
6.4	Interpretation and Use of Model Results	6-25
	6.4.1 Presentation of Model Results	6-26
	6.4.2 Use of Upper Bound Estimates	6-26
	6.4.3 Comparison of EPA and GE Models	6-29
7. A	ALTERNATIVE-SPECIFIC RISK ESTIMATES	
7.1	Alternative-Specific HHRA Issues	7-1
7.2	Alternative-Specific ERA Issues	7-9
8. C	COMMUNITY IMPACTS	
8.1	Transportation (Infrastructure)	8-1
	8.1.1 Rail	8-6
	8.1.2 River	8-7
	8.1.3 Road/Highway	8-8

Book	<u>1 of 3</u>	Page
8.2	Noise	8-10
8.3	Lighting	8-16
	8.3.1 Impact of Lighting on Livestock	
	8.3.2 Impact of Lighting on Community	
	8.3.3 Impact of Lighting on Agriculture and Ecological Resources	
8.4	Air Emissions	
	8.4.1 Odor	
	8.4.2 Diesel	
	8.4.3 PCB Transport (Particulates; Volatilization)	
8.5	Socioeconomic Issues	
	8.5.1 Aesthetics and Tourism	8-29
	8.5.2 Economics	8-36
	8.5.3 Quality of Life	
	8.5.4 Historic and Cultural Resources	
8.6	Siting of the Facilities	
	8.6.1 Site Selection Criteria	
	8.6.2 Implications of the Facilities	
8.7	Facility Operation	
	8.7.1 Staging of Dredged Sediments	
	8.7.2 Processing	
8.8	Remedy Health and Safety Issues	
	· ·	
9. IN	-RIVER IMPACTS (SHORT- AND LONG-TERM)	
9.1	Issues Related to SAV and other Ecological Resources	9-1
9.2	Effect on Water Quality	
9.3	Habitat Replacement	
9.4	Time to Recovery	9-41
9.5	Effect on Navigation Channel/Bathymetry	9-44
10. II	MPLEMENTABILITY OF REMEDIAL ALTERNATIVES	
10.1	Dredging Schedule and Production Rates	10-1
10.2	Monitoring	
10.3	Resuspension and Residual PCB Concentration	10-12
10.4	Backfilling and Shoreline Restoration	10-20
10.5	Dredged Materials Disposal	10-23
10.6	Safety Concerns	10-27
11. S	ELECTION OF THE PREFERRED REMEDY	
11.1	Overall Protection of Human Health and Environment	
11.2	Cost	
11.3	Long-term Effectiveness and Permanence	
11.4	Comparison Issues	
11.5	Benefits vs. Risks	11-12

<u>Book</u>	<u>1 of 3</u>	Page
11.6	Other	11-17
INDE	X	Index-1

TABLE OF CONTENTS

WHITE PAPERS (BOOK 2 of 3)

CONTAMINANT RISKS AND GEOCHEMISTRY

PCB Carcinogenicity

(MASTER COMMENT/RESPONSE 362702)

PCB Non-Cancer Health Effects

(MASTER COMMENT/RESPONSE 362704)

Relationship Between Tri+ and Total PCBs

(MASTER COMMENT/RESPONSE 424694)

Relationship Between PCB Concentration In Surface Sediments and Upstream Sources

(MASTER COMMENT/RESPONSE 255353)

Sediment PCB Inventory Estimates

(MASTER COMMENT/RESPONSE 363334)

Metals Contamination

(MASTER COMMENT/RESPONSE 253002)

Dioxin Contamination

(Master Comment/Response 860)

Model Forecasts for Additional Simulations in the Upper Hudson River

(MASTER COMMENT/RESPONSE 363150)

Application of the Depth of Scour Model (DOSM) in the Thompson Island Pool for Alternative Flooding Assumptions

(Master Comment/Response 407426)

Trends in PCB Concentrations in Fish in the Upper Hudson River

(MASTER COMMENT/RESPONSE 312627)

Relative Reduction of Human Health and Ecological Risks in the Mid- and Lower Hudson River

(MASTER COMMENT/RESPONSE 313699)

Resuspension of PCBs During Dredging

(MASTER COMMENT/RESPONSE 336740)

Human Health and Ecological Risk Reduction Under Phased Implementation

(MASTER COMMENT/RESPONSE 363176)

TABLE OF CONTENTS

Book 2 of 3

ENGINEERING FEASIBILITY

Example Sediment Processing/Transfer Facilities

(MASTER COMMENT/RESPONSE 253216)

Dredging Productivity and Schedule

(MASTER COMMENT/RESPONSE 253090)

Delays and Downtime

(MASTER COMMENT/RESPONSE 313398)

Post-Dredging PCB Residuals

(MASTER COMMENT/RESPONSE 312663)

Estimate of Dredged Material Exceeding TSCA Criteria

(MASTER COMMENT/RESPONSE 424851)

Rail Operations

(MASTER COMMENT/RESPONSE 312991)

Off-Site Disposal Of Processed Sediments

(MASTER COMMENT/RESPONSE 253477)

Additional Technology Evaluation

(MASTER COMMENT/RESPONSE 255314)

POTENTIAL IMPACTS OF THE SELECTED REMEDY

Potential Impacts to Water Resources

(MASTER COMMENT/RESPONSE 312851)

Coastal Zone Management

(MASTER COMMENT/RESPONSE 253238)

PCB Releases to Air

(MASTER COMMENT/RESPONSE 253202)

Air Quality Evaluation

(MASTER COMMENT/RESPONSE 313846)

Odor Evaluation

(MASTER COMMENT/RESPONSE 255361)

TABLE OF CONTENTS

Book 2 of 3

Noise Evaluation

(MASTER COMMENT/RESPONSE 312685)

Project-Related Traffic

(MASTER COMMENT/RESPONSE 253245)

River Traffic

(MASTER COMMENT/RESPONSE 337804)

Socioeconomics

(MASTER COMMENT/RESPONSE 313617)

INDEX

TABLE OF CONTENTS

This page left blank intentionally

TABLE OF CONTENTS

FIGURES, TABLES and APPENDICES (BOOK 3 of 3)

RESPONSES

Section 2 BACKGROUND AND REMEDIAL INVESTIGATION

Figure 573-1	Mass Fraction of PCB Homologue Groups in Water Column Samples from Transect 4 at Rogers Island During High Flow
Figure 573-2	Water Column Total PCB Annual Load at Fort Edward, TI Dam, and Schuylerville from GE Data (Ratio Estimator)
Figure 577-1	Net Annual Release to Total PCBs from Thompson Island Pool Sediments
Figure 617-1	PCB Load at Rt. 197 and Load Gain across the TIP (from GE data)
Figure 621-1	Cumulative Total PCB Load at River Mile 194.2 (Rogers Island) and
	River Mile 188.5 (TID-WEST), Estimated from GE Monitoring Data for April 1991-March 2000
Figure 621-2	Shift in PCB Homologue Pattern across the Thompson Island Pool,
8	Summer 1996
Figure 621-3	Summer Water Column Concentration at TID West versus Monthly
8	Average Flow at Fort Edward, 1996-1999
Figure 623-1	PCB Homologue Shift across the TIP, June-August 1997 GE Observations
Figure 623-2	Summer 1997 Water Column Relative PCB Congener Concentrations near
8	the Thompson Island Dam, Compared to Aroclor 1242
Figure 623-3	Congener Pattern in TIP Sediment Compared to Aroclor 1242
Figure 623-4	MDPR versus Total PCB Concentration for GE 0-5 cm Sediment
8	Concentrations in the Thompson Island Pool
Figure 623-5	Relative Percent Patterns in Water Column Gain at TIP-18C, Surface
8	Sediment, and Surface Sediment Porewater
Figure 623-6	Sediment Congener Pattern Derived from Summer 1997 Gain at TIP-18C
C	Attributed to Porewater Flux
Figure 623-7	Sediment Relative Concentrations Required to Support Observed Water
C	Column Concentrations via Porewater Flux
Figure 623-8	Concentrations at TID-West Predicted as a Mixture of Porewater and
C	Sediment Exchange
Figure 623-9	Concentration Gain at TIP-18C Predicted as a Mixture of Porewater and
C	Sediment Exchange
Figure 623-10	Relative Concentration Gain at TID-West, 1991-1997
Figure 623-11	1991-1997 Composite Congener Concentrations in TIP Load Gain
_	Predicted as a Mixture of Porewater and Surface Sediment
Figure 629-1	Concentration Trends in Brown Bullhead, Including 2000 Data
Figure 631-1	Ratio of Tri+ at Center Channel to TID-West, Plotted against Upstream
	Flow and Concentration
Figure 631-2	Monthly Total PCB Loads at Rt. 197 (Fort Edward) and Rt. 29
	(Schuylerville) Estimated from GE Data

TABLE OF CONTENTS

Book 3 of 3

Figure 633-1	Cumulative Frequency Distribution of Total PCB Concentration in
	Surface Sediments in the Thompson Island Pool, 1991 and 1998 GE Data
Figure 633-2	Cumulative Frequency Distribution of MDPR in Surface Sediments in the
	Thompson Island Pool, 1991 and 1998 GE Data
Figure 635-1	Annual Average PCB Tri+ Concentrations from USGS Monitoring at
	Waterford and Stillwater
Figure 641-1	Reproduction of Figure 3 from GE Comments, Appendix F.1
Figure 779-1	Total Organic Carbon in Sediment at RM 189 (TIP)
Figure 779-2	Brown Bullhead: Sediment Accumulation Factors
Figure 313787-1	Forecasts of White Perch Tri+ PCB Body Burdens from Farley Model
Figure 313787-2	Forecasts of White Perch Tri+ PCB Body Burdens from FISHRAND
Figure 313787-3	Forecasts of Largemouth Bass Tri+ PCB Body Burdens from FISHRAND
Figure 313787-4	Forecasts of Brown Bullhead Tri+ PCB Body Burdens from FISHRAND
Figure 313787-5	Forecasts of Yellow Perch Tri+ PCB Body Burdens from FISHRAND
Table 313787-1	Comparison of Tri+ PCB Concentrations-Water Column

Section 3 BASELINE RISK ASSESSMENTS AND PRGS

Figure 811-1	Risk Functions for Female Eagle Exposed to PCBs
Figure 811-2	Risk Functions for Female Mink Exposed to PCBs
Figure 811-3	Risk Functions for Female Otter Exposed to PCBs
Table 811-1	Summary of Measured PCB Concentrations in Liver of Mink and Otter
	Caught within 5 Miles of the Hudson River as Compared to TRVs
Table 811-2	Summary of Distributions and Distribution Parameters Used in Joint
	Probability Analysis

Section 4 REMEDIAL ACTION OBJECTIVES AND SELECTION OF TARGET AREAS

Figure 597-1	Correlations Among PCB Metrics for 1984 NYSDEC Sediment Survey
Figure 597-2	Correlations Among PCB Metrics for USEPA Low Resolution Sediment
	Coring Survey
Figure 597-3	Correlation of Surface Concentration and MPA for GE 1991 Composite
	Samples
Figure 597-4	Assessment of the Capture Efficiency for the Expanded Hotspot
	Remediation Tri+ PCB Concentration and MPA Histograms for 1984
	NYSDEC Data Within and Outside of Remedial Area
Figure 597-5	Assessment of the Capture Efficiency for the Expanded Hotspot
	Remediation Total PCB Concentration and MPA Histograms for 1984
	NYSDEC Data Within and Outside of Remedial Area
Figure 313219-1	Methodology for Volume Estimation

TABLE OF CONTENTS

Book 3 of 3

Section 5 TECHNOLOGY EVALUATION AND REMEDIAL ALTERNATIVE DEVELOPMENT

Figure 405965-1 Total PCB Content in Sediment vs. River Mile

Section 6 MODELING ASSUMPTIONS AND INTERPRETATION

Table 799-1	Mid Hudson River Species-Weighted Fish Fillet Average PCB
	Concentration (in mg/kg)
Table 799-2	Human Health Based Target Levels – Year Reached Comparison of
	Feasibility Study Alternatives – Mid-Hudson River
Table 799-3	Long-term Fish Ingestion Non-Cancer Hazards Reasonable Maximum
	Exposure and Central Tendency Mid-Hudson River-Adult Angler
Table 799-4	Long-Term Fish Ingestion Cancer Risks Reasonable Maximum Exposure
	and Central Tendency Mid-Hudson River – Adult Angler
Table 799-5	PCB Toxicity Quotients-Ecological Receptors 2011 on (25-
	Year Average) Mid to Lower Hudson River
Table 799-6	PCB Risk Reduction – Ecological Receptors (25-Year Average) Mid to
	Lower Hudson

Section 7 ALTERNATIVE-SPECIFIC RISK ESTIMATES

Table 797-1	Extended Dredging Fish Ingestion Non-cancer Health Hazards Reasonable
	Maximum Exposure and Central Tendency-Extended Dredging Upper
	Hudson River Fish-Adult Angler
Table 797-2	Extended Dredging Fish Ingestion Cancer Risks Reasonable Maximum
	Exposure and Central Tendency Upper Hudson River Fish-Adult Angler

Section 9 IN-RIVER IMPACTS (SHORT- AND LONG-TERM)

Figure 803-1 Average Monthly TSS Concentrations (mg/L)

Section 11 SELECTION OF THE PREFERRED REMEDY

Annual Tri+ PCB Loads at the Thompson Island, Northumberland, and
Federal Dams for Selected Years
Cumulative Tri+ and Total PCB Loads at the Thompson Island,
Northumberland, and Federal Dams (2004-2067)

TABLE OF CONTENTS

Book 3 of 3

WHITE PAPERS

CONTAMINANT RISKS AND GEOCHEMISTRY

Relationship Between Tri + and Total PCBs

Figure 424694-1	Relationship Between Ratio of Total PCBs to Tri+ and Tri+ Concentration
	in HR, LRC and GE Cores
Figure 424694-2	Estimation of Relationship Between the Ratio of Total PCBs to Tri+ and
	Tri+ Concentration
Table 424694-1	Total PCB to Tri+ for Upper Hudson Water Column Samples
Table 424694-2	Total PCB to Tri+ Ratios for the Sediments of the Upper Hudson
Table 424694-3	Homologue Fractions in 1993 Phase 2 Fish Results

Relationship Between PCB Concentrations in Surface Sediments and Upstream Sources

Figure 255353-1	PCB Concentration in High Resolution Sediment Cores in the Upper
	Hudson
Figure 255353-2	Expanded Scale PCB Concentration in High Resolution Sediment Cores in
	the Upper Hudson

Sediment PCB Inventory Estimates

Table 363334-1	PCB Mass Estimates using 1984 Thiessen Polygons, 1994 Phase 2 LRC
	and GE 1991 Composite Samples
Table 363334-2	Mean Length-Weighted Average Concentration Estimates using 1984
	Thiessen Polygons, 1994 LRC and GE 1991 Composite Samples
Table 363334-3	REM/0/0/3 in Section 1, In Situ Mass
Table 363334-4	REM 0/0/3 in Section 1, In Situ Average Concentration
Table 363334-5	Average Surface Concentration Estimates of Cohesive Sediments, in REM
	3/10/Select
Table 363334-6	Dredge Material Average Concentration Estimates

Metals Contamination

Figure 253002-1	Metals and Total PCBs in Two Dated Cores in Thompson Island Pool
Figure 253002-2	Metal Concentrations in Fish
Table 253002-1	Summary of Metal Levels in 1977 NYSDOH Sediment Samples
	(Tofflemire & Quinn, 1979)(mg/kg)
Table 253002-2	Summary of Metal Levels in Upper Hudson 1984 Cores (as reported by
	Brown et al., 1988) (mg/kg)

TABLE OF CONTENTS

Book 3 of 3

Table 253002-3	Summary of Metal Levels in 1986 and 1987 Hot Spot 3, 8, and 20 Cores (as reported by Brown <i>et al.</i> , 1988) (mg/kg)
Table 253002-4	Metal and PCB Concentrations in Bopp Sediment Cores (mg/kg)
Table 253002-4a	Comparison of Surface Concentrations Between 1991 (RM 188.6) and
	1993 (RM 203.3) data (mg/kg)
Table 253002-5	1983 and 1991 Thompson Island Pool Cores (as reported by McNulty,
	1997) (mg/kg)
Table 253002-6	Comparison of Metals Concentrations to Background Levels in 1993
	Samples (mg/kg)
Table 253002-7	Selected Physical Parameters and Mean Metal Concentrations (1993 Data)
Table 253002-8	1993 Ecological Risk Assessment Sediment Samples (0-5 cm) (mg/kg)
Table 253002-9	Results of Toxicity Characteristic Leaching Procedure (TCLP) on 1984
	and 1986 Sediment Samples
Table 253002-10	NYSDEC 1998 Fish Data-Selected Metals (ppm)
Table 253002-11	Summary of All Sediment Data Sets (1977-1993) (mg/kg)
Table 253002-12	Summary of Lower Interval 1983 Core and Baseline Sample

Dioxin Contamination

Table 860-1	Dioxins/Furans Concentration in the Bopp 1991 Core (RM 188.6) with
	Respect to TEQ Levels and Landfill Requirements (data provided by Bill
	Ports of NYSDEC)
Table 860-2	Results of TCDD, TCDF, and PCB Analyses of Sediments Collected in
	1983 from the Upper Hudson Rover (Brown et al., 1988)
Table 860-3	Results of 1987 TCDD, TCDF and PCB Analysis of HS 20 (Sample 1 &
	2), HS 8 (Samples 3 & 4), and HS 3 (Samples 5 & 6) (Brown et al., 1988)
Table 860-4	Hudson River Fish Dioxin/Furan Data

Model Forecasts for Additional Simulations in the Upper Hudson River

Figure 363150-1	Comparison Between Upper Hudson River Remediation Forecasts for
	Thompson Island Pool Cohesive Surficial Sediments
Figure 363150-2	Comparison Between Upper Hudson River Remediation Forecasts for
	Thompson Island Pool Non-Cohesive Surficial Sediments
Figure 363150-3	Comparison Between Upper Hudson River Remediation Forecasts for
	Schuylerville Cohesive Surficial Sediments
Figure 363150-4	Comparison Between Upper Hudson River Remediation Forecasts for
	Schuylerville Non-Cohesive Surficial Sediments
Figure 363150-5	Comparison Between Upper Hudson River Remediation Forecasts for
	Stillwater Cohesive Surficial Sediments
Figure 363150-6	Comparison Between Upper Hudson River Remediation Forecasts for
	Stillwater Non-Cohesive Surficial Sediments

TABLE OF CONTENTS

Book 3 of 3

Figure 363150-7	Comparison Between Upper Hudson River Remediation Forecasts for
F' 262150.0	Waterford Cohesive Surficial Sediments
Figure 363150-8	Comparison Between Upper Hudson River Remediation Forecasts for Waterford Non-Cohesive Surficial Sediments
Figure 262150 0	
Figure 303130-9	Comparison Between Upper Hudson River Remediation Forecasts for Federal Dam Non-Cohesive Surficial Sediments
Figure 363150-10	Comparison Between Upper Hudson River Remediation Forecasts for
1 1guic 303130 10	Thompson Island Dam Annual Average Tri+ PCB Water Column
	Concentration
Figure 363150-11	Comparison Between Upper Hudson River Remediation Forecasts for
8	Schuylerville Annual Average Tri+ PCB Water Column Concentration
Figure 363150-12	Comparison Between Upper Hudson River Remediation Forecasts for
C	Stillwater Annual Average Tri+ PCB Water Column Concentration
Figure 363150-13	Comparison Between Upper Hudson River Remediation Forecasts for
	Waterford Annual Average Tri+ PCB Water Column Concentration
Figure 363150-14	Comparison Between Upper Hudson River Remediation Forecasts for
	Federal Dam Annual Average Tri+ PCB Water Column Concentration
•	Predicted Fish Body Burdens 2004 - 2010
_	Predicted Fish Body Burdens 2004 - 2067
0	Predicted Fish Body Burdens for White Perch
Figure 363150-18	Comparison of Predicted Species-Weighted Fish Body Burdens Across
E: 262150 10	Different Assumptions of the Selected Remedy 2004 - 2064
Figure 363150-19	Comparison of Predicted Species-Weighted Fish Body Burdens Across Different Scenarios 2004 - 2064
Figure 363150 20	Comparison of Predicted Species-Weighted Fish Body Burdens Across
11gure 303130-20	Different Scenarios 2004 – 2010 (2015 for RM 154)
Table 363150-1	Comparison of HUDTOX Modeling Scenarios Conducted to Evaluate
14010 303130 1	Alternative Selected Remedy (REM-3/10/Select) Assumptions
Table 363150-2	REM-3/10/Select Remedial Scenario Dredging Sequence Information
	Used to Develop HUDTOX Inputs for 5-Year and 6-Year Implementation
	Periods
Table 363150-3	Dredging-Induced Daily Tri+ PCB Load for REM-3/10/Select and a Five-
	Year Implementation Schedule (Run R14RS) Input to HUDTOX Water
	Column Segments
Table 363150-4	Dredging-Induced Daily Tri+ PCB Load for REM-3/10/Select and a Six-
	Year Implementation Schedules (Runs R20RS @0.13% and R20RX
T 11 060170 7	@2.5%) Input to HUDTOX Water Column Segments
Table 363150-5	Tri+ PCB Load Over Thompson Island Dam
Table 363150-6	Tri+ PCB Load Over Northumberland Dam
Table 363150-7	Tri+ PCB Load Over Federal Dam

TABLE OF CONTENTS

Book 3 of 3

Application of the Depth of Scour Model (DOSM) in the Thompson Island Pool for Alternative Flooding Assumptions

Table 407426-1	Summary of Hydrodynamic Model Predictions for RBMR (47,330 cfs) and Estimated Upper Limit (61,835 cfs) 100-Year Peak Flows
T 11 407406 0	
Table 407426-2	Poolwide Thompson Island Pool Average Surficial Sediment
	Concentrations
Table 407426-3	Shear Stresses at High-Resolution Core Locations
Table 407426-4	Erosion Depth Comparison at High-Resolution Core Locations
Table 407426-5	Thompson Island Pool Expected Values of Solids Erosion and Mean
	Depth of Scour
Table 407426-6	Thompson Island Pool (TIP) Expected Values of Tri+ PCB Erosion in
	Comparison to PCB Inventory Estimates
Table 407426-7	Thompson Island Pool (TIP) Expected Values of Total PCB Erosion in
	Comparison to PCB Inventory Estimates

Trends in PCB Concentrations in Fish in the Upper Hudson River

Figure 312627-1	Lipid-based Tri+ PCB Concentrations in Fish, Thompson Island Pool
	(RM 189) (Revised)
Figure 312627-2	Lipid-based Tri+ PCB Concentrations in Fish, Stillwater Reach (Revised)
Table 312627-1	Half-Life Comparison of Model and Data Lipid-Based Annual Average
	PCB Concentrations in Fish

Relative Reduction of Human Health and Ecological Risks in the Mid- and Lower Hudson River

Table 313699-1	Mid-Hudson River Species-Weighted Fish Fillet Average PCB
	Concentrations (mg/kg)
Table 313699-2	Long-Term Fish Ingestion Cancer Risks Mid-Hudson River - Adult
	Angler
Table 313699-3	Long-Term Fish Ingestion Non-Cancer Hazard Indices Mid-Hudson River
	– Adult Angler
Table 313699-4	Modeled Times (Years) of Compliance with Human Health Risk-Based
	Concentrations Mid-Hudson River
Table 313699-5	Lower Hudson River Whole Fish Largemouth Bass Average PCB
	Concentrations (mg/kg)
Table 313699-6	Lower Hudson River Whole Fish Spottail Shiner Average PCB
	Concentrations (mg/kg)
Table 313699-7	Average (25-year) PCB Toxicity Quotients – Ecological Receptors
Table 313699-8	Modeled Times of Compliance with Ecological RGs and Risk-Based
	Concentrations

TABLE OF CONTENTS

Book 3 of 3

Resuspension of PCBs During Dredging

Figure 336740-1	Fraction of Total Constituent Loss in Dissolved Form (K _d =10 ⁵ L/kg)
Figure 336740-2	Typical Silt Curtin Response to Current
Figure 336740-3	Frequency Distribution of Resuspension Rates for Cutterhead Dredging
_	Operations
Figure 336740-4	Location of SMU 56/57 and Sample-Collection Sites
Figure 336740-5	Dissolved-Phase PCB Congener Distribution for the Upstream and
_	Downstream Sites, Fox River, Wis.
Figure 336740-6	Mean Dissolved and Particulate Effluent PCB Congener Concentrations
	on the Fox River, Wis.
Figure 336740-7	PCB Concentrations at the Upstream and Downstream Transects Before
	and During Dredging Operations, Fox River, Wis.
Figure 336740-8	Daily Mean Total Suspended Solids Concentrations for Upstream and
	Downstream Transects, Fox River, Wis.
Figure 336740-9	Daily Water-Column PCB Load in the Deposit Area During the Dredging
	Operation on the Fox River, Wis.
Figure 336740-10	New Bedford Harbor Monitoring Stations
Figure 336740-11	General Electric Company-Hudson River Project Post-Construction
	Remnant Deposit Monitoring Program - Pump House Sediment Removal
	Interim Remedial Measures Site Map
_	Homologue Distribution from Hudson Falls IRM Monitoring Activities
Figure 336740-13	Resuspension Rate for Open Clamshell Bucket Dredges with Water Depth
	Estimation of the Rate of Downstream Transport due to Resuspension
Table 336740-2	Characteristics of Cutterhead Field Studies Used to Estimate Resuspension
	Rates
Table 336740-3	Summary of PCB Concentration (ppm) ¹ in Sediment After Dredging
Table 336740-4	Cumulative PCB Mass Transport (kg)
Table 336740-5	Summary of Estimated Resuspension Losses from Clamshell (open)
	Bucket Operations

Human Health and Ecological Risk Reduction Under Phased Implementation

Table 363176-1	Selected Remedy (REM-3/10/Select) Upper Hudson Species-Weighted
	Fish Fillet Average PCB Concentration (mg/kg)
Table 363176-2	Selected Remedy (REM-3/10/Select) Scenarios Post-Remediation PCB
	Concentrations in Fish-Upper Hudson River
Table 363176-3	Selected Remedy (REM-3/10/Select) Scenarios – Long-Term Fish
	Ingestion Reasonable Maximum Exposure and Central Tendency Cancer
	Risks Upper Hudson River Fish – Adult Angler
Table 363176-4	Selected Remedy (REM-3/10/Select) Scenarios – Long-Term Fish
	Ingestion Reasonable Maximum Exposure and Central Tendency PCB
	Non-Cancer Hazard Indices Upper Hudson River Fish – Adult Angler

TABLE OF CONTENTS

Book 3 of 3

Table 363176-5	Modeled Times (Years) of Compliance with Human Health Risk-Based
	Concentrations Selected Remedy (REM-3/10/Select) Scenarios
Table 363176-6	Largemouth Bass Whole Body Average PCB Concentrations (mg/kg)
Table 363176-7	Spottail Shiner Whole Body Average PCB Concentrations (mg/kg)
Table 363176-8	Selected Remedy (REM-3/10/Select) Scenarios Average PCB Toxicity
	Quotients Ecological Receptors (25-Year Time Frame)
Table 363176-9	Modeled Times of Compliance with Ecological Risk-Based
	Concentrations Selected Remedy (REM-3/10/Select) Scenarios

ENGINEERING FEASIBILITY

Example Sediment Processing/Transfer Facilities

Example Northern Sediment Processing and Transfer Facility Site -
Existing Conditions
Example Southern Sediment Processing and Transfer Facility Site -
Existing Conditions
Example Northern Sediment Processing and Transfer Facility - Layout for
Mechanical Dredging
Example Southern Sediment Processing and Transfer Facility - Layout for
Mechanical Dredging
Example Northern Sediment Processing and Transfer Facility - Layout for
Hydraulic Dredging

Dredging Productivity and Schedule

Table 253090-1 "Other Projects" (Hydraulic) Referenced in Comments

Delays and Downtime

Table 313398-1	Analysis of Daily Temperature Information
Table 313398-2	Analysis of River Flow Delays

Estimate of Dredged Material Exceeding TSCA Criteria

Figure 424851-1	Cumulative Percentage of Sediment Volume Removal based on Total	
	PCB Concentration with TI Pool	
Table 424851-1	Percentage of Material Exceeding TSCA Criterion of 32 mg/kg	

Additional Technology Evaluation

Table 255314-1 List of Process Options for Bioremediation

TABLE OF CONTENTS

Book 3 of 3

POTENTIAL IMPACTS OF THE SELECTED REMEDY

Potential Impacts to Water Resources

Figure 312851-1	Typical Total Nitrogen and Total PCB Profiles in the Upper Hudson River
	High Resolution Core Samples
Figure 312851-2	Hudson River PCBs Site Existing Discharge Locations to the Upper
	Hudson
Table 312851-1	Model-Based Estimates of TSS from Resuspension for the Hudson River
Table 312851-2	Estimated Total Nitrogen Increase in the Water Column during Dredging
Table 312851-3	Estimate Total Phosphorous Increase in the Water Column during
	Dredging
Table 312851-4	Estimated Flux of Metals to the Water Column, Based on the
	Resuspension Model at 10 Meters Downstream of the Dredge Head
Table 312851-5	Estimated Concentrations for Metals in the Water Column
Table 312851-6	Estimated Flux of PAHs to Water Column, Based on the Resuspension
	Model at 10 Meters Downstream of the Dredge Head
Table 312851-7	Estimated Concentrations for PAHs in the Water Column at the Waterford
	Intake
Table 312851-8	Estimated Dissolved Oxygen Impacts Due to Dredging

Coastal Zone Management

Figure 253238-1	Project site relative to the New York State-designated coastal zone
Figure 253238-2	Average Monthly TSS concentrations for Schuylerville, Stillwater and
	Waterford New York plotted against the estimated project-related fully
	mixed TSS concentration for hydraulic and mechanical dredging (0.50
	mg/L and 1.1 mg/L) for River Sections 2 and 3
Table 253238-1	Freshwater, Brackish Water, and Salt Water Habitats

PCB Releases to Air

Table 253202-1	Estimated Transfer Area of the Components for Mechanical Dredging at
	the Sediment Processing/Transfer Facility
Table 253202-2	Estimated Transfer Area of the Components for Hydraulic Dredging at the
	Sediment Processing/Transfer Facility
Table 253202-3	ISCST3 Model Options
Table 253202-4	Calculated PCB Loss from the Sediment Treatment/Transfer Facilities
Table 253202-5	Predicted PCB Levels at the Modeled Receptor Locations and Associated
	Standards
Table 253202-6	Predicted PCB Levels at the Modeling Receptor Locations Near Dredging
	Site and the Ambient Standard
Table 253202-7	Outside Facility Boundary Cancer Risks to Residents

TABLE OF CONTENTS

Book 3 of 3

Table 253202-8	Outside Facility Boundary Non-Cancer Hazards to Residents
Table 253202-9	Inside Facility Boundary Cancer Risks to Adult Workers
Table 253202-10	Inside Facility Boundary Non-Cancer Hazards to Adult Workers

Air Quality Evaluation

Table 313846-1	National and New York Ambient Air Quality Standards
Table 313846-2	Diesel Equipment Emission Rates
Table 313846-3	Truck Emission Rate
Table 313846-4	Sediment Handling Emission Rate
Table 313846-5	ISCST3 Model Options
Table 313846-6	Worst-Case Total Impact from Mechanical Dredging at NTF
Table 313846-7	Worst-Case Total Impact from Hydraulic Dredging at NTF
Table 313846-8	Worst-Case Total Impact Along the Hudson River from a Stationary
	Booster Near Glenn Falls Area
Table 313846-9	Worst-Case Total Impact Along the Hudson River from a Stationary
	Booster Near Albany Area
Table 313846-10	Calculated Metals Concentrations Associated with Airborne Suspended
	Particles

Odor Evaluation

Table 255361-1	Calculated H ₂ S Levels and Relevant Standards
Table 255361-2	Calculated NH ₃ Levels and Relevant Standards

Noise Evaluation

Table 312685-1	FHWA Noise Abatement Criteria
Table 312685-2	Typical Peak Noise Emission Levels for Construction Equipment
Table 312685-3	Long-term Noise Levels from Sediment Processing and Transfer Facilities
Table 312685-4	Long-term Noise Levels from Stationary Booster
Table 312685-5	Predicted Short-term L _{eq} (1) (dBA) Noise Levels from Mechanical
	Dredging Process (worst-case ten weeks)
Table 312685-6	Predicted Short-term L _{eq} (1) (dBA) Noise Levels from Hydraulic Dredging
	Process (worst-case nine weeks)

Project-Related Traffic

Table 253245-1	Fuel Deliveries Required Per Week
Table 253245-2	Truck Deliveries for the Northern Transfer Facility
Table 253245-3	Estimate of Traffic from Northern Transfer Facility

TABLE OF CONTENTS

Book 3 of 3

River Traffic

Table 337804-1	Recent Trends in Bulk Commodity Traffic on the Upper Hudson River
Table 337804-2	Projected Mechanical Dredging Equipment Requirements
Table 337804-3	Projected Hydraulic Dredging Equipment Requirements
Table 337804-4	1999 Champlain Canal Traffic Data
Table 337804-5	Available Lockages for 2001 Operating Season on the Hudson River (per
	lock)
Table 337804-6	Available Lockages Assuming 24 Hours of Operation
Table 337804-7	Daily Lockages at Lock 5-Schuylerville-Based on Peak Month (July 1999)
Table 337804-8	Daily Lockages at Lock 6-Fort Miller-Based on Peak Month (July 1999)
Table 337804-9	Estimated Lock Traffic at Lock 5 and 6 During Mechanical Dredging
	Removal Operations Occurring in River Section 1 and River Section 2
Table 337804-10	Daily Lockages (July 1999) vs. Daily Proposed Project Lockages, Lock 6
	 Mechanical Dredging
Table 337804-11	Daily Lockages (July 1999) vs. Daily Proposed Project Lockages, Lock 5
	 Mechanical Dredging
Table 337804-12	Daily Lockages (July 1999) vs. Daily Proposed Project Lockages, Lock 6
	 Hydraulic Dredging

Socioeconomics

Figure 313617-1	Unemployment Rates
Figure 313617-2	Unemployed
Figure 313617-3	Construction Employment 1989-1998
Table 313617-1	Input Expenditures
Table 313617-2	Output Impacts – Five-County Region
Table 313617-3	Earning Impacts – Five-County Region
Table 313617-4	Employment Impacts – Five-County Region
Table 313617-5	Tourism Employment and Wages 1988-1999
Table 313617-6	Studies on Property Value Impacts

NO FIGURES OR TABLES

Rail Operations

(MASTER COMMENT/RESPONSE 312991)

PCB Carcinogenicity

(MASTER COMMENT/RESPONSE 362702)

PCB Non-Cancer Health Effects

(MASTER COMMENT/RESPONSE 362704

TABLE OF CONTENTS

Book 3 of 3

Off-Site Disposal Of Processed Sediments (MASTER COMMENT/RESPONSE 253477)					
Post Dredging PCB Residuals (Master Comment/Response 312663)					
APPENDICES					
APPENDIX A	- HUDSON RIVER PCBs SUPERFUND SITE PRELIMINARY WETLANDS ASSESSMEN				
APPENDIX B	- HUDSON RIVER PCBs SUPERFUND SITE PRELIMINARY FLOODPLAINS ASSESSM				
APPENDIX C	- STAGE 1A CULTURAL RESOURCES SUF	RVEY			
		Page			
	Γ				
	CTION				
	Description				
	History				
	s of Remedial Action				
1.4 Gene	eral Objectives and Organization of Document				
2. REGULATO	ORY FRAMEWORK				
2.1 Appl	icable Statutes and Regulations				
	ey Methods				
3 PEMEDIAI	ACTION ALTERNATIVES	C-13			
	eription of Alternatives				
	eral Removal Information				
	cted Remedy				
4 ENWIDONIA	IENTAL SETTING	C 21			
	iologyial History				
	rology				
•	ments				
	DIC AND HISTORIC DACKCROUND	0.27			
	RIC AND HISTORIC BACKGROUND				
	istoric Period				
5.2 Pre-I	Industrial Era, ca. 1609-1815				

Book 3 of 3 Pag			Page
	5.4 20th Century	, ca. 1900-1945	. C-55
		1945-Present	
6.	RESULTS OF SURV	/EY	. C-67
	6.1 National Regi	ster-Listed Resources	. C-67
	6.2 National Regi	ster-Eligible Resources	. C-68
	6.3 Unevaluated l	Resources	. C-69
	6.4 Previous Stud	ies	. C-71
	6.5 Other Resource	ces	. C-79
7.	POTENTIAL EFFEC	CTS OF SELECTED REMEDY	. C-81
	7.1 Effects to Kno	own National Register-Listed and Eligible Resources	. C-83
		haeological Resources	
	7.3 Effects to Oth	er Resources	. C-88
8.	FUTURE STEPS		. C-89
	8.1 Identification	and Evaluation Efforts	. C-89
	8.2 Mitigation of	Adverse Effects	. C-90
	8.3. Coordination		. C-91
ΒI	BLIOGRAPHY		C-93
AF	PPENDIX C TABLES &	FIGURES	
	Figure C.1-1	Overview of Upper Hudson River Glen Falls to Federal Dam	
	Figure C.2-1	Upper Hudson River APE	
	Figure C.3-1 A & B	Alternative REM-3/10/Select Removal Areas and Depths	
	Figure C.3-1 C & D	Alternative REM-3/10/Select Removal Areas and Depths	
	Figure C.3-1 E & F	Alternative REM-3/10/Select Removal Areas and Depths	
	Figure C.3-1 G	Alternative REM-3/10/Select Removal Areas and Depths	
	Figure C.3-1 H	Alternative REM-3/10/Select Removal Areas and Depths	
	Figure C.3-1 I & J	Alternative REM-3/10/Select Removal Areas and Depths	
	Figure C.3-1 K & L	Alternative REM-3/10/Select Removal Areas and Depths	
	Figure C.4-1	Land Form Regions for New York State	
	Figure C.4-2	Land Form Categories for New York State	
	Figure C.4-3	Hydrography on Upper Hudson River	
	Figure C.4-4	Underlying Rock Formation for New York State	
	Figure C.5-1	New Netherlands and New England, 1635	
	Figure C.5-2	New Netherland, 1621	
	Figure C.5-3	Major Land Grants and Patents of Colonial New York	
	Figure C.5-4	New York Counties, Colonial Era, 1776	
	Figure C.5-5	Northern Campaigns of the Revolutionary War	

TABLE OF CONTENTS

Book 3 of 3

Figure C.5-6	Confluence of Hudson and Mohawk Valleys, 1843		
Figure C.5-7	Canals of New York in 1855		
Figure C.5-8	Upper Hudson River & Surrounding Region, 1880		
Figure C.5-9	West Shore and New York Central Railroad		
Figure C.5-10	Delaware and Hudson Railroad		
Figure C.5-11	Upper Hudson River, 1921		
Figure C.5-12	New York State Barge Canal System, 1925		
Figure C.5-13	Hudson River Valley Electric Railway, 1906		
Figure C.6-1 A	Architectural & Archaeological Resources in Upper Hudson River APE		
Figure C.6-1 B	Architectural & Archaeological Resources in Upper Hudson River APE		
Figure C.6-1 C	Architectural & Archaeological Resources in Upper Hudson River APE		
Figure C.6-1 D	Architectural & Archaeological Resources in Upper Hudson River APE		
Table C-1a	National Register-Listed Resources in Albany County		
Table C-1b	National Register-Listed Resources in Rensselaer County		
Table C-1c National Register-Listed Resources in Saratoga County			
Table C-1d	able C-1d National Register-Listed Resources in Warren County		
Table C-1e	C-1e National Register-Listed Resources in Washington County		
Table C-2	Previously-Identified Archaeological Sites in Area of Potential Effect		
Table C-3	Prior Archaeological Surveys		

APPENDIX D - COMPENDIUM OF PUBLIC COMMENTS

APPENDIX D COMPACT DISKS

Database of Public Comments	Compact Disk D1
Public Comment Documents	Compact Disks D2 – D6

TABLE OF CONTENTS

This page left blank intentionally

LIST OF ACRONYMS AND ABBREVIATIONS

ACGIH American Conference of Governmental Industrial Hygienists

ACHP Advisory Council on Historic Preservation

AGC Annual Guideline Concentration AOC Administrative Order on Consent

ANOVA Analysis of Variance

APEG Alkaline (Alkali Metal Hydroxide) Polyethylene Glycol ARAR Applicable or Relevant and Appropriate Requirement

ARCC Adirondack Regional Chambers of Commerce

ARCS Assessment and Remediation of Contaminated Sediments Program

ATSDR Agency for Toxic Substance and Disease Registry

AWQC Ambient Water Quality Criterion
BAT Best Achievable Technology
BBL Blasland, Bouck, and Lee
BCD Base-Catalyzed Decomposition
BMR Baseline Modeling Report

CADD Computer-Aided Drafting and Design

CDF Confined Disposal Facility
CDI Chronic Daily Intake

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

CFR Code of Federal Regulations

cfs cubic feet per second

CIP Community Interaction Program

CLU-IN Hazardous Waste Clean-up Information (EPA web site)

COC Chemical(s) of Concern

COPC Chemical(s) of Potential Concern

CSF Cancer Slope Factor
CSM Conceptual Site Model
CT Central Tendency
CWA Clean Water Act

CZM Coastal Zone Management

DEIR Data Evaluation and Interpretation Report

DMR Discharge Monitoring Report
DNAPL Dense Non-Aqueous Phase Liquid

DOC Dissolved Organic Carbon DOSM Depth of Scour Model

DOT Department of Transportation
DRE Destruction and Removal Efficiency

ECD Electron Capture Detector

ECL Environmental Conservation Law (New York)
EE/CA Engineering Evaluation/Cost Analysis

EEC Extreme Effect Concentration
EIS Environmental Impact Statement

EO Executive Order

EPA Environmental Protection Agency
EPC Exposure Point Concentration
ERA Ecological Risk Assessment
ESA Endangered Species Act

ETWG Engineering/Technology Work Group FAIR Farmers Against Irresponsible Remediation

LIST OF ACRONYMS and ABBREVIATIONS (cont'd)

FDA Food and Drug Administration

FEMA Federal Emergency Management Agency

FR Federal Register

FRTR Federal Remediation Technologies Roundtable

FS Feasibility Study

FSSOW Feasibility Study Scope of Work FWIA Fish & Wildlife Impact Analysis

g/m² Grams per meter squared
GAC Granular Activated Carbon
GC Gas Chromatography
GCL Geosynthetic Clay Liner
GE General Electric Company
GIS Geographic Information System

GLNPO (EPA's) Great Lakes National Program Office

GRA General Response Action
HDPE High Density Polyethylene
HHRA Human Health Risk Assessment

HHRASOW Human Health Risk Assessment Scope of Work

HI Hazard Index

HMTA Hazardous Materials Transportation Act

hp Horsepower HQ Hazard Quotient

HROC Hudson River PCB Oversight Committee

HSI Habitat Suitability Index

HTTD High Temperature Thermal Desorption HUDTOX Upper Hudson River Toxic Chemical Model

IBI Index of Biotic Integrity

IRIS Integrated Risk Information System

ITT Innovative Treatment Technologies (database)

kg Kilogram

KPEG Potassium polyethylene glycol

LOAEL Lowest Observed Adverse Effect Level LRC, LRCR Low Resolution Sediment Coring Report

LTI LimnoTech, Inc.

LTTD Low Temperature Thermal Desorption

LWA Length-Weighted Average

MANOVA Multivariate Analysis of Variance

M&E Metcalf and Eddy

MBI Macroinvertebrate Biotic Index MCA Menzie-Cura and Associates

MCACES Cost Estimating Software (USACE)
MCL Maximum Contaminant Level
MCLG Maximum Contaminant Level Goal

MDEQ Michigan Department of Environmental Quality

MDPR Molar Dechlorination Product Ratio MEC Mid-Range Effects Concentration

mg/kg Milligrams per Kilogram (generally equivalent to parts per million, or ppm)

mg/L Milligrams per Liter (generally equivalent to ppm)

MNA Monitored Natural Attenuation

MPA Mass per Unit Area

LIST OF ACRONYMS and ABBREVIATIONS (cont'd)

MS Mass Spectroscopy

NAAQS National Ambient Air Quality Standards NAICS North American Industry Coding System

NAS National Academy of Sciences

NCP National Oil Spill and Hazardous Substances Pollution Contingency Plan

NEPA National Environmental Policy Act ng/L Nanograms per Liter, parts per trillion NHPA National Historic Preservation Act NiMo Niagara Mohawk Power Company

NOAA National Oceanic and Atmospheric Administration

NOAEL No Observed Adverse Effect Level

NPL National Priorities List NRC National Research Council

NTCRA Non-Time Critical Removal Action NYCRR New York Code of Rules and Regulations

NYSDEC New York State Department of Environmental Conservation

NYSDOH New York State Department of Health NYSDOL New York State Department of Labor

NYSDOT New York State Department of Transportation

NYSPDES New York State Pollutant Discharge Elimination System

O&M Operation and Maintenance

OPRHP Office of Parks, Recreation, and Historic Preservation OSHA Occupational Safety and Health Administration

OSWER Office of Solid Waste and Emergency Response (EPA)

OU Operable Unit

PCB Polychlorinated Biphenyl

PCRDMP Post-Construction Remnant Deposit Monitoring Plan

PEL Probable Effects Level

PMCR Preliminary Modeling Calibration Report
ppm part(s) per million (mg/kg or mg/L)
PRG Preliminary Remediation Goal

PSG Project Sponsor Group PVC Polyvinyl Chloride

RAMP Remedial Action Master Plan RAO Remedial Action Objective RBC Risk-Based Concentration

RBMR Revised Baseline Modeling Report

REACH IT Remediation and Characterization Innovative Technologies (EPA database)

RfD Reference Dose

RI/FS Remedial Investigation/Feasibility Study

RI Remedial Investigation

RIMS Remediation Information Management System

RM River Mile

RME Reasonable Maximum Exposure

ROD Record of Decision

SARA Superfund Amendments and Reauthorization Act of 1986

SAV Submerged Aquatic Vegetation SEC Sediment Effect Concentration SHPO State Historic Preservation Office

SITE Superfund Innovative Technology Evaluation Program

SPDES State Pollution Discharge Elimination System

LIST OF ACRONYMS and ABBREVIATIONS (cont'd)

SQRT Screening Quick Reference Tables STC Scientific and Technical Committee

T&E Threatened and Endangered TAG Technical Assistance Grant

TAGM Technical Assistance Guidance Memorandum (NYSDEC)

TBC To-be-considered

TCDD 2,3,7,8-Tetrachlorodibenzo-p-dioxin

TCP 2,4,6-Trichlorophenol

TEC Threshold Effect Concentration
TEF Toxicity Equivalency Factor

TEQ (Dioxin-like) Toxic Equivalent Quotient

TI Thompson Island
TID Thompson Island Dam

TIN Triangulated Irregular Network

TIP Thompson Island Pool
TLV Threshold Limit Value
TOC Total Organic Carbon

TOGS Technical and Operational Guidance Series (NYSDEC)

TOPS Trace Organics Platform Sampler

TQ Toxicity Quotient TR Target Risk

TRV Toxicity Reference Value
TSCA Toxic Substances Control Act
TWA Time-Weighted Average
UCL Upper Confidence Limit
UET Upper Effects Threshold

μg/kg Micrograms per Kilogram, (generally equivalent to parts per billion, or ppb)
μg/L Micrograms per Liter, (generally equivalent to parts per billion, or ppb)

USACE United States Army Corps of Engineers
USBEA United States Bureau of Economic Analysis
USBLS United States Bureau of Labor Statistics

USC United States Code

USDOC United States Department of Commerce
USDOD United States Department of Defense
USDOE United States Department of Energy
USDOI United States Department of Interior
USFWS United States Fish and Wildlife Service

USGS United States Geological Survey

VISITT Vendor Information System for Innovative Treatment Technologies (EPA

Program)

VLDPE Very Low Density Polyethylene WHO World Health Organization

Hudson River PCBs Site Record of Decision Responsiveness Summary

EXECUTIVE SUMMARY

INTRODUCTION

Since its inception in 1990, EPA's Reassessment Remedial Investigation/Feasibility Study (RI/FS) has had the benefit of an extensive public-involvement program. Even before the initiation of the formal public comment period on the Proposed Plan for the Hudson River PCBs Superfund Site and the supporting analysis and information, there had been over 65 meetings/forums with the public, involving many issues, people, and places. It was through this extensive effort that EPA determined that local landfilling of dredged materials would not be an option in the event that a dredging remedy were selected.

EPA opened the formal public comment period with the release of the Hudson River PCBs Superfund Site Proposed Plan on December 12, 2000. The Proposed Plan presented EPA's preferred remedy and the rationale for its selection. The preferred remedy consisted of removal (targeted dredging) of 2.65 million cubic yards of contaminated sediments containing over 150,000 pounds of PCBs from the Upper Hudson River using environmental dredging techniques that would minimize adverse environmental impacts, including the resuspension of sediments. The comment period, originally scheduled to close on February 16, 2001, was extended to April 17, 2001. During the comment period, EPA chaired 11 public meetings that were attended by thousands of individuals, several hundred of whom provided oral comment. By the close of the comment period, EPA had received 73,215 discrete submissions of comments, of which nearly half were e-mails. As multiple individuals signed some submissions, the number of commenters is recorded as over 90,000 individuals.

The results of this public involvement program and EPA's response to the concerns raised are clearly evident in the Record of Decision (ROD), which is being released at this time. Some of the more notable examples of decisions that reflect public comment on the Proposed Plan include:

- A commitment to develop (with input from the affected public) a comprehensive public involvement program to be employed throughout the design and construction phases of the project.
- A commitment to develop, during the design phase (with input from State and federal agencies, as well as the public), performance standards for key project aspects, including sediment resuspension and dredging production rates.
- A commitment to perform the construction in a phased manner whereby a first phase of construction (one construction season) will precede the full-scale, five-year construction period.

- A commitment to include in the first phase, in addition to project shakedown, the field verification of various project assumptions.
- A commitment to move dredged materials and backfill within the Upper Hudson River area
 by barge or rail to ensure that disruption of traffic patterns in neighboring communities does
 not occur.

The aforementioned are some of the more significant aspects of the decision or ROD that have been aimed at responding to concerns raised throughout the public comment period. Other quality-of-life factors, such as noise, odor, maintenance of navigation, water supply protection, construction lighting, air quality, aesthetics, maintenance of recreational opportunities, and impacts on farm activities, also have been taken into account within the selected remedy and are addressed in detail within this Responsiveness Summary (RS). What follows in this Executive Summary is an abbreviated discussion of some of these issues. For each, a more detailed discussion can be found within the main body of the RS.

PUBLIC INVOLVEMENT IN DESIGN AND CONSTRUCTION

A number of comments dealt with the necessity of developing and implementing a comprehensive and detailed public involvement plan for the remedial design and implementation phases of the Hudson River PCBs Site cleanup.

Since the beginning of the Reassessment, EPA has been committed to a public process that is fully open to any interested party. The original community interaction plan (CIP) was designed to be flexible so that it could be modified in response to changes dictated by the project or requested by the participants. Since 1990, EPA has modified not only the CIP but also certain aspects of the RI/FS itself, as well as the selected remedy, based on public input.

EPA continues to be committed to involving the public, this time throughout the project's design (including development of performance standards and the sediment processing/transfer facility siting process) and construction phases. In the near future, EPA will involve the community in the development of a project-tailored public process that allows for incorporation of public involvement throughout the design and construction phases of the project and fully considers input received.

RESUSPENSION

Many comments addressed the potential for PCB release to the water column during remedial dredging operations. Concerns over the extent and impact of releases caused by resuspension of contaminated sediments on public health and the environment have been raised. In reviewing these concerns, EPA agrees that such releases must be carefully balanced with impacts associated with ongoing PCB releases to the water column from the sediments and existing impacts to the aquatic biota. After a thorough review of available dredging equipment, EPA concludes that conventional hydraulic cutterhead dredges and enclosed environmental bucket dredges are best suited to the selected remedial dredging activity. Data from projects using these dredges were used as the basis for estimating water quality impacts that would result during dredging operations. These data show loss rates adjacent to the dredge head of 0.35 percent (by mass of fine sediments) for a conventional

hydraulic cutterhead dredge and 0.3 percent (by mass of fine sediments) for an environmental bucket dredge.

During the first year of project design, with input from State and federal agencies as well as the public, EPA will develop the details of performance standards and performance monitoring that will be utilized during the first phase of project construction to field verify and modify, as appropriate, project operations.

PROJECT SEQUENCE AND SCHEDULE

Many commenters questioned the viability of EPA's schedule for accomplishing the selected remedy. EPA will begin the initial steps toward implementation once the ROD is signed. These pre-remediation activities, including project design, are scheduled for completion by Spring 2005, and many of these activities will be performed simultaneously. They include the following:

- Development of performance standards.
- Additional sediment sampling and analysis.
- Evaluation and selection of dredging technologies.
- Selection of contractor(s).
- Sediment processing/transfer facility siting and construction.
- Finalization of agreements with landfills, rail companies, backfill material suppliers, and energy providers.
- Mobilization (*e.g.*, assembling of equipment, planning the materials-handling operation, and arranging for sediment transportation and disposal).

Dredging operations will commence during the 2005 canal season.

Some commenters requested that EPA consider smaller, more focused projects, or perform a demonstration dredging project, to determine the feasibility of the selected remedy. EPA did, in fact, consider the possibilities of a short-term demonstration project and smaller-scale remedial efforts in the Upper Hudson River. Modeling indicated that smaller-scale efforts would not substantially reduce the PCB concentrations in fish.

In the Proposed Plan for this project, EPA proposed a five-year schedule for the work, beginning in the year 2004. However, given the concerns expressed by commenters, the Agency has decided to implement the project using a phased approach. Performing dredging operations in this manner provides the opportunity to evaluate overall project performance more intensively at the beginning and, as appropriate, refine the operations, which are now planned over a six-year period.

The selected remedy will be conducted in two phases over the six-year schedule. The first phase of dredging, to begin in 2005, will be implemented during the first construction season. The dredging during that year will be implemented initially at less than full-scale operation, and will include an extensive monitoring program based on performance standards that will address (but may not be limited to):

- Resuspension rates during dredging.
- Production rates.
- Residuals after dredging.
- Community impacts (e.g., noise, air, odor, navigation).

Data gathered during this first phase will enable EPA to determine if adjustments are needed to operations in the succeeding phase of dredging or if performance standards need to be reevaluated. The current schedule assumes that, after the phased-in operations of 2005, dredging operations will proceed at full scale in the years 2006, 2007, 2008, and 2009, with completion of remaining work in 2010.

Similarly, commenters questioned the plausibility of achieving targeted dredging rates with the dredging equipment selected. EPA considered available technologies in combination with a series of Site-specific factors such as sediment characteristics, river geometry, in-river transportation systems, and environmental constraints in arriving at likely production rates. EPA concludes that the production rates generated by examination of these factors are considered practical and attainable.

Commenters also compared EPA's productivity estimates to lower rates actually attained at other Superfund sites. EPA believes that project scale and Site-specific conditions render such comparisons technically invalid.

QUALITY OF LIFE FACTORS

With regard to concerns expressed about the potential for negative impacts to the quality of life of people residing near or utilizing the river in the vicinity of the remediation, EPA has made every effort to fully assess and address such issues. They are summarized below in the categories of traffic, noise, construction lighting, air quality, odor, aesthetics, and recreation.

While there may be short-term impacts with respect to some of these issues, the project will follow strict guidelines to minimize and mitigate potential impacts to the maximum extent practicable.

It is EPA's belief that any temporary impacts are manageable and far outweighed by the long-term benefits of the remediation on human health and the environment.

Traffic

Commenters raised concerns about the ability of the existing infrastructure to accommodate project-related increases in vehicular and truck traffic, and the potential disruption to regional roadways that could result from these increases. In response to these concerns, EPA has determined that dredged materials will be taken from the Site by barge and/or rail, rather than by truck. Likewise, material used for project backfill will be transported within the Upper Hudson River area by barge and/or rail. While the location(s) of the sediment processing/transfer facilities have not yet been determined, for purposes of the FS and Responsiveness Summary, northern and southern facility sites were assumed.

Impacts from vehicle and truck traffic caused by both worker commutation and construction of dredged-material processing facilities were the key elements of concern remaining, once trucking of dredged material and backfill was eliminated. At the southern sediment processing/transfer facility site, impacts will be easily manageable, because much of that locale is currently highly industrialized and experiences much greater activity than would be generated by project operations.

For the northern facility, estimates of the project-related road traffic were evaluated in the context of current traffic volumes and road capacities. During peak traffic conditions, it was concluded that employee traffic generated by the project will not be disruptive to the area's local communities, because the volume increase on nearby roadways will be minor (*i.e.*, less than 10 percent). Given that this increase in road usage is relatively small, it is unlikely that there will be an escalation in road hazards or a need for increased road maintenance as a result of implementing the selected remedy.

Noise

The short-term noise associated with construction of the sediment processing/transfer facilities and hydraulic and mechanical dredging operations will not exceed the New York State Department of Transportation- (NYSDOT) established construction impact guidelines.

With respect to noise associated with operation of the sediment processing/transfer facilities, such noise levels will comply with applicable federal and State criteria, including the Federal Highway Administration (FHWA) Noise Abatement Criteria (NAC). While the long-term noise associated with stationary booster pump operations under the hydraulic dredging option could, if not mitigated, exceed FHWA NAC in areas within an 800-ft radius of the booster, a series of mitigation measures (e.g., noise attenuation shrouds, optimizing locations of the booster stations to avoid populated areas to the extent practicable, or use of electric pumps) can be implemented as appropriate to mitigate the impact.

Construction Lighting

Artificial lighting systems will be used to illuminate nighttime dredging and in-river transport operations, as well as land-based sediment processing/transfer facility operations. EPA has examined the types of artificial lighting that will likely be used in support of the project. Positioning of lights, brightness, and direction are key factors in minimizing the potential for off-site impacts.

While nighttime lighting requirements for the proposed work will conform to established industry safety standards, it will not be necessary to use high-mast lighting systems at dredging sites or at the sediment processing/transfer facilities. The lighting required for in-river transport will conform to the Coast Guard and New York Navigation Law standards for commercial towboats and barges and is not expected to be disruptive. Lighting at the land-based sediment processing/transfer facilities will meet OSHA standards for construction. Lighting will be directed toward work areas and away from neighboring properties. In addition, the use of low-mast lights will limit off-site glare.

Odor

The two potential sources of odor from the project are the construction equipment and the dredged material from the river itself.

Nuisance odors from construction equipment are not anticipated to be a significant problem, because such equipment is used routinely on most construction projects with few complaints. Although sulfur in a reduced form is present in the river sediments, concentrations are sufficiently low so as to preclude the generation of noticeable and persistent odors from hydrogen sulfide in dredged material. Further, no significant ammonia-related odor will be generated during dredging operations. Should any odor be encountered, strategies will be implemented to mitigate adverse effects.

Air Quality

The total concentration of pollutants from the dredging and sediment processing/transfer facility operations will not exceed the National Ambient Air Quality Standards (NAAQS) established by EPA to protect public health. It is not anticipated that the project will have a significant air quality impact.

The cancer risks associated with inhalation of volatilized PCBs in air by residents living near the river or near the sediment processing/transfer facilities are projected to be about an order of magnitude *below* the most stringent acceptable level. With respect to workers at the Site, the estimated cancer risk is within the acceptable risk range. Air monitoring, engineering controls, appropriate personal-protection equipment for workers, and standard safety procedures will be used to protect the on-site workers and nearby communities.

With the public involved, EPA will develop and implement a comprehensive community health and safety plan, including air monitoring, to address any potential risk associated with dredging and processing of the PCB-contaminated sediment.

Aesthetics

Potential aesthetic and visual impacts from the dredging will apply to only a small portion of the 40 miles of river and, where they do occur, will be very temporary. Such potential impacts from the sediment processing/transfer facilities will be limited by the siting of these facilities in industrial or commercial regions and apply only to areas of close proximity; these impacts will be minimized, to the extent practicable, by careful siting and design of these sites. For travelers on the river or moving along adjacent roadways, project-generated visual intrusion will be short-term and limited to within several hundred feet of the work area.

Recreation

Because of the relatively small area of the river that will be affected by dredging at any given time, the recreational experience on the river will remain substantially unaffected in areas not immediately adjacent to the dredging operation. In fact, it is expected that the project will improve recreational conditions. Few adverse impacts are anticipated for recreational boaters during implementation of

the selected remedy. A significant portion of the dredging is oriented to navigational dredging that, when completed, will provide an expanded and safer capacity for recreational use of the river.

The risk of swimming in the Hudson River, as discussed in the baseline Human Health Risk Assessment (HHRA), is considered to be within the acceptable range. It is anticipated that during the remediation project, PCB concentrations in the river will remain at or near current levels. Therefore, during the project, as now, the risk of swimming in the river will remain within the acceptable range.

It is anticipated that the impact on recreational fishing will be minimal during the remediation. Anglers will be able to find alternate sites to fish where the dredging and backfill operations are not proximate; impacts to fish habitat will be temporary and will affect only limited areas and certain species; and minor, temporary resuspension of PCBs during dredging should not affect catch-and-release fishing. In fact, the PCB remediation offers long-term prospects of renewed and enhanced recreational fishing.

SEDIMENT PROCESSING/TRANSFER FACILITY SITING AND DESIGN

EPA has not yet determined the location(s) of sediment processing/transfer facilities necessary to implement the selected remedy. For purposes of the FS, example locations were identified from an initial list of candidate sites based on screening-level field observations that considered potential facility locations from an engineering perspective. In the FS, it was necessary to assume the locations of sediment processing/transfer facilities in order to develop conceptual engineering plans, analyze equipment requirements, and develop cost estimates for the remedial alternatives. For this purpose, two example locations were identified: one at the northern end of the project area in the vicinity of the Old Moreau Dredge Spoil Area site and another at the southern end of the project area near the Port of Albany. Each of these example locations fulfills many of the desired engineering characteristics for such a facility to support the remedial work, and is representative of reasonable assumptions with regard to distance from the dredging work and cost. Other locations, both within the Upper Hudson River area and farther downstream, are possible.

The example facility locations presented in the FS have also been used in this Responsiveness Summary in order to clarify material presented in the FS and Proposed Plan and in connection with additional noise, odor, and other analyses that were performed in order to respond to public comments. EPA will not determine the actual facility location(s) until after EPA performs additional analyses and holds a public comment period on proposed locations and considers public input in the final siting decision. Thus, all information provided in this Responsiveness Summary relative to potential impacts of the sediment processing/transfer facilities on communities, residents, agriculture, the environment, and businesses should likewise be considered representative and illustrative. Further specific assessment of and, as necessary, mitigation of, potential impacts will be addressed during design.

The general engineering characteristics that can be useful in identifying a potential site include a waterfront location so that barges and other floating equipment may be accessed; an existing heavy-duty bulkhead; fairly level topography to keep transfer operations, material processing, and rail facilities at approximately the same elevation; an industrial or commercial site, to avoid impacting residential, recreational, and institutional land uses; access to areas for storage of project-related

equipment; roadway access for both construction equipment and employees that avoids densely populated residential communities; two-lane roadways to accommodate truck traffic, or direct connection to such routes; and rail access to facilitate hauling and reduce overall transportation costs.

Already-developed industrial areas are preferable for consideration in siting these facilities. It is not anticipated that residences will be affected by processing/transfer of dredged material at these sites.

Potential impacts from the facilities on surroundings will be mitigated by attention to facility design and layout; lighting; screening and buffering of the facility; and minimization of truck traffic, among other considerations. Although it is expected that these facilities will be land-based, water-based facilities will also be evaluated.

PCB TRENDS IN FISH AND WATER COLUMN

While it is true that levels of PCB contamination in all Upper Hudson River media have declined relative to the early 1980s, most of the decline was prior to 1985. In recent years there has been limited improvement and, in fact, PCB levels have remained relatively consistent. The conditions in the river were extremely poor in the late 1970s, largely due to events such as the breaching of the Fort Edward Dam. After the resulting massive influx of PCBs, EPA has documented that PCB levels in the river declined until 1985, which was approximately the time the Agency issued its original plan for the river – no action – in the hope that levels would continue to decline.

Since that time, however, the rate of improvement has leveled off, and substantial further improvement via natural attenuation does not appear to be occurring. For this reason, EPA has concluded that active remediation is needed to restore the Hudson River to a healthy ecosystem. To support this conclusion, further information on PCB concentrations in specific media is presented below.

- Water column concentrations: In general, PCB concentrations in the water column declined between 1991 and 1995 due to source control but, due to the continued, unabated input of PCBs from the sediment, little change has occurred over the past five years.
- Sediment concentrations: While sediment PCB concentrations have slowly declined on average, the response is very heterogeneous and does not solve the contamination problem. Even though concentrations have declined in some areas, high concentrations remain at or near the surface in many of the *hot spots*. The stability of PCBs that are currently buried in sediment cannot be assured, and it is the position of both EPA and an independent peer-review panel that the sediments of the Upper Hudson River do not represent a secure location for the long-term storage of PCBs.

Examination of PCB stability in sediment is complicated by the fact that modeling cannot accurately compensate for the variety of conditions within a river reach. For example, while the Thompson Island Pool is considered to be net depositional, specific highly contaminated areas are clearly not consistently depositional. Further, the presence of deposition does not ensure the stability and sequestration of the PCBs contained within the contaminated sediments. Evidence from multiple sources indicates that PCBs are not being safely buried to

a degree sufficient to remove them from interaction with the Hudson River.

Fish concentrations: Despite the leakage of unweathered PCB oil from the vicinity of the GE
Hudson Falls facility having been largely controlled, PCB concentrations in fish tissue have
shown little decline in recent years (up to the year 2000). Sampling studies and modeling of
such concentrations indicate continuing exposure through sediment food-chain pathways.

BENEFITS OF PROJECT

EPA's decision to pursue the selected remedy balanced short-term impacts against long-term benefits. In doing so, the Agency examined three active remediation alternatives and two more-passive options: the No Action and the Monitored Natural Attenuation (MNA) Alternatives.

Under the "overall protection of human health and the environment" criterion (40 CFR § 300.430[e][9][iii][A]), EPA evaluated the degree to which the remedial alternatives provide adequate protection of human health and the environment from unacceptable risks posed by PCBs at the Site, and compared the relative protection afforded by each alternative.

Based on the comparative analysis of alternatives, EPA determined that active remediation of contaminated sediments is necessary in order to significantly reduce the human health and environmental risks at the Site. Unlike the selected remedy, the alternatives that do not require removal of PCB-contaminated sediments are not sufficiently protective. Similarly, EPA's analysis of the more extensive remedy (REM-0/0/3) found the differential in protection from that afforded by the selected remedy was insufficient to justify the greater cost of REM-0/0/3. There may be short-term impacts as a result of implementation of the selected remedy, including potential transportation, noise, odor, and lighting impacts, as well as potential impacts from construction and operation of the sediment processing/transfer facilities. However, these temporary impacts are expected to be manageable through appropriate controls. Consequently, EPA has determined that the potential short-term impacts of the selected remedy, which can be minimized, are substantially outweighed by the remedy's benefits to human health and the environment.

Projected PCB Trends in Fish

Because PCBs bioaccumulate in fatty tissue, PCB levels in fish of the Hudson River has been a critical factor in this project and a critical issue for the public. Commenters frequently asked how many years would be required to attain the preliminary remediation goal (PRG) for human health, which is 0.05 ppm (mg/kg) PCBs in fish or other target levels. Commenters also observed that, and at times questioned why, this goal is 40 times stricter than the US Food and Drug Administration's commercial fish limit of 2.0 ppm. Others asked when the fish would be 'edible.'

Attainment of Target Levels

The time it takes to achieve the Remediation Goal of 0.5 mg/kg PCBs in fish fillet and other risk-based PCB concentrations in fish (i.e., 0.4 mg/kg and 0.2 mg/kg) is species- and location-specific. Some fish will achieve these concentrations sooner than others, based on feeding and habitat preferences. The modeling projects that the selected remedy will attain the PCB concentration of 0.4

mg/kg in fish fillet, which is protective of the average adult who consumes one Hudson River fish meal every two months, in River Sections 1 and 2 within 20 years after the start of active remediation and earlier for River Section 3. The modeling also projects that the target PCB concentration of 0.2 mg/kg in fish fillet, which is protective of an adult who consumes one fish meal from the Hudson River per month, is expected to be attained in River Section 2 within 35 years of the start of active remediation. These time periods are significantly shorter than the time periods projected for attaining these targets under the No Action and the MNA Alternatives. Moreover, the actual time differentials may be greater than those calculated by EPA's models, as evidenced by the trend analysis of recent PCB concentrations in fish tissue.

The selected remedy is projected to meet the Remediation Goal for human consumption of fish, 0.05 mg/kg, in River Section 3 within 41 years of completion of active remediation. As a result, the remediation goal of 0.05 mg/kg, or one fish meal per week for an adult, also is expected to be attained in the majority of the Lower Hudson River within this time frame, due to the lower initial concentration of PCBs in the Lower Hudson compared to the Upper Hudson. Because of the continuing Tri+ PCB load of 2 ng/L assumed after implementation of the source control action in the vicinity of the GE Hudson Falls plant, the PCB concentration in fish averaged over the Upper Hudson is expected to be reduced to a range of 0.09 to 0.14 mg/kg within the 70-year modeled time period, which is slightly above the PRG of 0.05 mg/kg. However, the protectiveness of the selected remedy is further enhanced through continuation of institutional controls, such as the fish consumption advisories and fishing restrictions. In the ROD, EPA has adopted the 0.05 mg/kg concentration in species-weighted fish fillet as a final Remediation Goal for the Site.

If upstream source control is more successful than currently projected (*i.e.*, less than 0.025 kg/day), then the time frames identified above would be shorter and the Remediation Goal of 0.05 mg/kg may be met within the modeling time period in River Sections 1 and 2.

FDA Limit/Establishment of Target Level

The FDA tolerance level of 2.0 ppm is based on a "market basket" of commercially caught fish obtained from supermarkets. The "market basket" concept assumes that fish purchased from a market come from varied sources, rather than from a sole source, such as fish taken from the Hudson River. The 2.0 ppm tolerance level in commercially marketed fish is an average PCB concentration, and assumes that consumers are buying a variety of different species from a variety of different locations.

The Remediation Goal of 0.05 mg/kg PCBs in fish fillet represents an average PCB concentration in fish and takes into account the specific expected reasonable maximum exposure (RME) consumption rate of anglers who consume fish caught only from the Hudson River. These consumption rates reflect the habits reported by anglers in New York State and what would be expected in the absence of fish consumption advisories. It should also be noted that the Remediation Goal of 0.05 mg/kg is consistent with the Great Lakes Sport Fish Advisory level, which is used by the eight states bordering the Great Lakes.

Downstream Transport

PCBs are transported from the Upper Hudson River to the Lower Hudson River (i.e., south of the

Federal Dam at Troy). The mass of PCBs transported over the Federal Dam to the Lower Hudson declined from about 3,000 to 4,000 kg/year Tri+ PCBs (6,610 to 8,820 lbs/year) in the late 1970s to about 150 to 500 kg/year Tri+ PCBs (331 to 1,100 lbs/year) by the late 1980s or early 1990s. The most recent estimate of Tri+ PCBs, based on 1998 GE data from a monitoring station at Schuylerville, is 214 kg/year (472 lbs/year); the estimated (modeled) average for the 1990s is about 290 kg/yr (639 lbs/year) over Federal Dam, with a modeled daily average Tri+ PCB water column concentration of 30 ng/L. It is projected that the selected remedy will reduce downstream transport by approximately 40 percent.

GE SOURCE CONTROL ACTIVITIES

Over a 30-year period, GE discharged a significant amount of PCBs into the river from its Hudson Falls and Fort Edward plants. At the Hudson Falls plant location, leakage of PCB-bearing oils through bedrock to the river continues to be a source of PCB contamination.

The selected remedy accounts for the fact that some source control measures are already in place near the GE Hudson Falls plant. Additionally, pursuant to a Consent Order with the NYSDEC, additional source-control work is to be carried out by GE near its Hudson Falls plant because PCBs continue to leak from that facility into the Upper Hudson River. Therefore, the selected remedy also assumes reasonable further reduction in PCBs entering the river through bedrock at Bakers Falls near the Hudson Falls plant, as a result of the implementation of these additional source control measures.

Through detailed monitoring, EPA found that PCB levels in the water column (and consequently, PCB mass load) increase more than threefold as the water passes through the Thompson Island Pool. The PCB source available in this location is the contaminated sediments that lie on the pool's bottom.

Concerns about Identification of Additional Sources

As reflected in the Phase 1 Report, EPA recognized the importance of upstream sources of PCBs from the outset of the Reassessment. From an analysis of sampling data gathered by GE's monitoring program in accordance with an EPA Consent Order, EPA has established that the GE facilities are the only significant external source of PCBs to the Upper Hudson River. Modeling efforts, including use of the HUDTOX and FISHRAND models, indicate that control of upstream sources is critical. However, recognition of these upstream sources does not in any way negate the findings of recent EPA reports noting that the sediments continue to release large amounts of PCBs.

As described in the FS, control of the upstream source is an important adjunct to the active remediation of the contaminated river sediment. The anticipated controls at GE's Hudson Falls facility and remediation in the vicinity of the Fort Edward 004 outfall should reduce that input within the next few years. EPA acknowledges the importance of further remediation of upstream sources and will work with NYSDEC and GE to control these sources to the extent practicable. However, given existing PCB sediment loads, complete control of these upstream sources is not necessary prior to sediment removal.

WHY A MORE AGGRESSIVE REMEDY WAS NOT SELECTED

EPA's analysis found that:

- The incremental increase in water column loading from the sediments decreases as the water moves downstream from the Thompson Island Pool. This suggests that there is less sediment involved in PCB release in the downstream river sections relative to the Thompson Island Pool.
- The model forecasts showed little improvement in recovery of the river for REM-0/0/3 as compared to the selected remedy. This analysis suggests that little benefit comes from the additional dredging.
- As described in the FS and in this Responsiveness Summary, the targeted areas include more
 than 85 percent of the areas with PCB concentrations greater than 10 ppm and more than 75
 percent of the areas with PCB concentrations greater than 3.2 ppm. Going beyond this one
 would encounter problems such as greater access limitations and shallow underlying
 bedrock, which greatly increase costs while yielding little additional public health or
 environmental benefit.

After considering all these factors, EPA decided upon the selected remedy as an appropriate balance among these issues, reconciling the desire to remove contamination with the uncertainties associated with each river section. Note, however, that the final areas and boundaries will be refined during remedial design.

RAIL TRANSPORT

EPA is committed to avoiding large increases in the volume of heavy truck traffic in communities of the Upper Hudson River valley. The selected remedy provides for rail transport or barge transport. The necessity for rail access at sediment processing/transfer facility sites has been incorporated into the facility-planning process.

In studying rail transport of the processed materials, EPA estimated the rail movement that will occur in order to implement the selected remedy in the context of the capacity and current operation of the regional rail line operated by the Canadian Pacific Railroad (CPR).

Increased train volumes are not expected to impact passenger or non-project-related freight service in the region. There are currently six passenger trains and up to 14 freight trains per day (through and local) operating along the Fort Edward/Albany rail corridor. This level of activity does not approach the capacity of the line. After speaking with representatives of the CPR, it has been determined that the current Fort Edward/Albany rail line, dominated by freight service, has additional capacity available on the line.

With regard to rail-yard requirements for the northern processing/transfer facility, it would be necessary to store 16 gondola cars on-site. There would be daily pickups of these gondolas by the railroad. It is expected that existing rail yards in the project vicinity can be used to store rail cars and

assemble larger trainloads for movement to remote landfill sites; CPR has indicated that their existing rail yard facilities can accommodate gondola cars generated by the project, as well as the daily transport and assembly of these railcars into unit trains.

No new rail yards are expected to have to be constructed in the region to support the proposed activities. The availability of rail cars/gondolas in the region has also been assessed, with the determination that the number of gondolas required for the project can be obtained by leasing them on the open market; therefore, CPR will not necessarily provide them. It has also been determined that current rail car leasing costs are low due to market demand; many are actually being scrapped at this time. The shipping of three commodities, specifically Toxic Substances Control Act (TSCA)-regulated materials, non-TSCA materials and backfill, adds moderately to the project's complexity, but will be manageable.

This page left blank intentionally

INTRODUCTION TO THE RESPONSIVENESS SUMMARY

By the conclusion of the public comment period on April 17, 2001, EPA received nearly 73,000 separate, individual statements providing comment on its December 2000 Proposed Plan for the Hudson River PCBs Site. This number includes several thousand replicate statements, which are identical pieces submitted by multiple individuals, or petitions signed by multiple individuals, but does not include carbon copies or duplicates of the same message sent to multiple recipients within EPA or to other agencies. Of these 73,000 statements, approximately 35,000 were in the form of e-mails directed to EPA's project team. The remainder was received in the form of letters (some typed, but many handwritten), post cards, form letters, multi-page documents and technical reports, videotaped statements, and petitions on various media. A number of the technical reports contain appendices covering specific issues in depth. The largest body of comment was received from General Electric Company and occupies 19 volumes.

Given these circumstances, three basic steps have been followed in preparing a Responsiveness Summary that is responsive to all significant public comments received during the public comment period: (1) all comment documents were reviewed and catalogued, (2) the material was organized for content, all significant comments were identified, and each such comment was either individually adopted as a "master comment," or was combined with other significant comments (addressing similar issues) which were then collectively distilled into a single master comment, and (3) a response was prepared for each master comment.

A quality assurance program was implemented to verify that the full body of significant comment is accurately represented in the master comments, the responses are technically sound and the entire summary is internally consistent. The process by which these three steps and the attendant quality assurance processes were accomplished is summarized as follows.

Each of the comment letters and other documents was reviewed, and individual significant comments within each comment document were delimited (*i.e.*, identified). A single comment document may contain as few as one or as many as several hundred delimited comments. Each of the unique comment source documents was assigned a bar-coded identification number which was affixed to the document¹ and was then scanned as an image into an electronic file compatible with *Adobe Acrobat Reader*TM software (*i.e.*, "pdf" format), effectively creating an electronic "photocopy." Approximately 18,000 unique significant comments were delimited from the source documents.² Because of the large number of comments to manage, each of the delimited comments was also assigned representative keywords (or key phrases) and entered into an electronic database for sorting and processing.

Introduction-1

¹ Only a single example of each set of perfectly identical submittals (*i.e.*, replicates – for example, postcards provided to its members by an organization) was bar-coded for entry to the database. However, a record was compiled of the names and, where supplied, addresses of all commenters. Such mailings were individually bar-coded in those instances where additional comment was added to the text by the commenter. True duplicates (*i.e.*, multiple copies of the same document sent by the same individual, sometimes transmitted to multiple recipients) were bar-coded only once and the identity of the commenter recorded only once.

² While some documents yielded multiple delimited comments, others were replicates of other identical documents which together yielded a single comment. This total represents the number of "unique" significant comments.

Some comments were received electronically or could readily be scanned (via optical character recognition, or OCR) for entry into the database. Many delimited significant comments, however, required manual entry. Quality assurance reviews were conducted to ensure that all comments were entered in the database. There is a high degree of confidence that all significant comments were identified and captured.

Due to the large volume of comments received, it is not possible to present these documents as physical (hard copy) attachments to the Responsiveness Summary, as has customarily been done for previous Hudson River PCBs Site Responsiveness Summary reports. Each comment is, however, provided in electronic format on a set of CDs in Appendix D, along with tables identifying authors and showing the relationships between authors, delimited significant comments and master comments. For copies of the Responsiveness Summary provided entirely on CD, the comments are included as separate files.

Similar or related delimited comments were combined into master comments in various topical areas capturing the significant issues raised by each of the source comments.³ A total of 274 master comments were synthesized from the roughly 18,000 comments initially delimited. These master comments were then reviewed for accuracy and thoroughness to ensure that they represent each of the associated delimited comments. In addition, a review was conducted to verify that all delimited comments were associated with at least one master comment. Because of the several threads of thought sometimes inextricably combined, an individual delimited comment may be, on occasion, associated with multiple master comments. This process has provided a means for all significant comments to be included and to receive due consideration in preparing the Responsiveness Summary.

Master comments have been organized according to topical areas for presentation in this volume (Book 1) of the Responsiveness Summary, as shown in the Table of Contents. A response has been prepared for (and is presented immediately following) each of the master comments, drawing from material presented in the Proposed Plan, the FS, or other previous project reports, other literature, remedial projects and individuals, and EPA policy, as well as additional technical analyses performed specifically to address comments or questions raised during the public comment period. Methodologies used and results obtained from additional technical analyses are presented as "white papers" in a separate volume (designated as Book 2 of this document). These papers cover a variety of topical areas, providing more in-depth analysis and supporting detail concerning topics addressed in various comments. Many responses draw upon these white papers and may utilize the conclusions or quantitative results of various modeling efforts (for noise or air emissions, for example) or extended series of calculations, without encumbering the text with voluminous detail. Each of the responses and white papers has been reviewed for technical quality by senior professionals within the project team.

³ Master comments were assigned a three- or six-digit identification number by the database program sequentially upon creation; these numbers are used to identify the master comments, the associated responses, and any companion tables and figures throughout the Responsiveness Summary, regardless of the final order of presentation in the document. White papers are similarly identified.

⁴ Additional technical analyses were performed for several reasons, including refinement or clarification of work performed in the FS, gathering and evaluating additional data from outside sources and other projects to clarify or support conclusions or statements made in the FS, and providing information not ordinarily presented in an FS but which is appropriate to address public comment germane to the community acceptance criterion of the remedy selection analysis.

While some smaller tables have been embedded in the text of a response or white paper, most larger tables and figures have been placed in a separate volume dedicated to that purpose (designated as Book 3 of this document). This allows the reader (if using the printed version of the document) to view the associated tables and figures alongside the text, without having to turn back and forth in the document. Book 3 also contains Appendices to the Responsiveness Summary. These include a Preliminary Wetlands Assessment (Appendix A), a Preliminary Floodplains Assessment (Appendix B), and a Stage 1A Cultural Resources Survey (Appendix C). These Appendices provide additional information relating to potential impacts of the selected remedy on wetlands, floodplains, and cultural resources. The Appendices also are pertinent to issues addressed in Book 1 of the Responsiveness Summary. Appendix D is described below.

Significant effort has been made to make this document as user-friendly as practicable, while covering the full body of significant comment. It is anticipated that many readers will want to find where their particular comment or concern is addressed. An important tool in this search is the Index at the end of this volume. The Index allows a reader to identify master comments and responses of interest, based on keywords or key phrases. While an attempt has been made to cover a comprehensive range of subjects and as much detail as practicable in the Index, it is not intended to be exhaustive. Despite the topical arrangement of the document, and provision of the Index, some readers may need to resort to the comment database to identify the code associated with a comment of interest, and then track this code through a table of associations between delimited significant public comments and master comments provided on CD# D1 in Appendix D in Book 3 of the Responsiveness Summary. While neither the Index nor the table of associations is a perfect tool, together they provide a reliable means of finding the responses to particular comments. Appendix D, Compendium of Public Comments, provides a compilation of the public comments in electronic database form. Appendix D consists of a set of instructions to the database as well as a set of six CDs, which contain the database of authors and comments (Disk D1) and scanned images of the public comments (Disk D2 to D6).

This page left blank intentionally

Keywords	Master Comment (Report Section)
Adverse Impacts	421 (11.5), 505 (8.5.1), 713 (1.3)
Energy Use	
Equipment Failure	
Agriculture	
Air Quality Impacts	
Processing and Transfer Facility	· /
Alternative Technologies	, 1
ARARs	,
	399 (1.1), 401 (1.1), 407 (1.1),
	447 (3.3), 503 (1.1), 313682 (1.1),
	365240 (1.2.1), 407625 (1.1)
CERCLA	` ''
Coastal Zone Management (CZM)	` '
Fish and Wildlife Coordination Act (FWCA)	
Fish Population	
Legal Issues	· · ·
Lighting	
Odor	
Source Control	555 (1.1)
Water Quality	
Wetlands	491 (11.4)
Wetlands	· · · · · · · · · · · · · · · · · · ·
Assumptions	652 16 (1.1)
Resuspension	
Residual Concentrations	
PCB Transport to Lower	
Hudson River	591 (6.1.4)
Backfill	` /
Dredging	
Habitat Replacement	313373 (9.3)
Habitat Replacement	
Submerged Aquatic Vegetation (SAV)	51355 (7.5)
Wetlands	313365 (9.3)
Barge Operations	513505 (7.15)
Canal Corporation	
Navigation	
Socioeconomic Impacts	337804 (w.n.)
Baseline Ecological Risk Assessment (BERA)	
Assumptions Assumptions	
Risk Benefit	
PCB Exposure	793 (3.2.3)
Ecological Risk Assessment (ERA)-analysis	173 (3.4.3)
Peer Review	811 (3.2)
Inday 1	, ,
Indox 1	

Human Health Risk Assessment (HHRA)	
Support of Dredging	
Source Control	.813 (3.2.1)
Remedial Alternatives	, ,
Wetlands	
Biota	815 (3.2.2)
Benthic Habitat	.010 (3.2.2)
Epifaunal	525 (9.3)
Bioaccumulation	.525 (7.5)
Recovery Time	
•	
Ecological Risk Assessment (ERA)-analysis	
FISHRAND	.785 (6.2)
Bioavailability	
PCB Concentrations in Sediment	
PCB Burial	
Benthic Habitat	.637 (2.3)
Biodegradation	
Bioaccumulation	
PCB Toxicity	.253430 (2.3)
Dechlorination	
Bioremediation	.255314 (w.p.)
Biota	` 1 /
Hydraulic Dredging	
Submerged Aquatic Vegetation (SAV)	
Water Quality	366264 (9.1)
Bioturbation	.30020+ (7.1)
Fate and Transport	
PCB Burial	252424 (2.2)
	.233424 (2.3)
Canal System	
Socioeconomic Impacts	212042 (0.1.2)
Transportation	
Capping	
Long Term Effectiveness and Permanence	.337788 (11.1)
Natural Attenuation	
Erosion	.651 (5.1.1)
Remedial Alternatives	.313835 (5.2)
CERCLA	
National Contingency Plan (NCP)	.475 (1.2.1)
Remedy Selection	
Coastal Zone Management (CZM)	
Lower Hudson	
Community Acceptance	(1.2.1)
Public Participation	
<u>*</u>	123154 (1 2 1)
Record of Decision (2001 ROD)	
Support of Dredging	.443 (1.3)

Consensus Based Guidelines	
Adverse Impacts	795 (3.3)
Cost Effective	
Disposal	· · ·
Effectiveness of Implementability Cost	
Other Sites	
Legal Issues	` '
Definition of Onsite	303920 (11.2)
CERCLA	721 (1 2 1)
	· · · · · · · · · · · · · · · · · · ·
Dioxins and Furans	` * /
Disposal	
Dredging	
Adverse Impacts	
Dredging Technology	
Remedy Selection	657 (5.1.3)
Habitat Replacement	
Backfill	513 (9.3)
Processing and Transfer Facility	
Treatment	` '
Residual Concentrations	579 (10.3)
Dredging Technology	
Alternative Technologies	423845 (5.1.3)
Hydraulic Dredging	
Resuspension	
Sedimentation	366262 (5.1.3)
Manufacture of Commercial Products	
Remedial Alternatives	364760 (5.1.3)
Drinking Water Supply	
PCB Concentrations in Water	, ,
PCB Transport to Lower Hudson River	365942 (9.2)
PCB Discharge	
Ecological Risk Assessment (ERA)-analysis	
Human Health Risk Assessment (HHRA)	
Risk Benefit	
Remedial Alternatives	363176 (w n)
Peer Review	
Risk Benefit	105 (115.11)
Biota	817 (7.2)
Ecological Risk Assessment (ERA)-impacts	017 (7.2)
Ecological Risk Assessment (ERA)-analysis	
Flood	800 (3.2.2)
Effectiveness of Implementability Cost	607 (3.2.2)
Remedial Alternatives	313083 (5.2)
	313703 (3.4)
Endangered Species Act (ESA)	259464 (1.1)
ARARs	330404 (1.1)

EPA's Contaminated Sediment Management Strategy	
Remedial Alternatives	313990 (6.4.1)
Safety Impacts	
Equipment Selection	
Dredging Technology	659 (10.1)
Fate and Transport	,
Phase 1	
Phase 2	575 (2.3)
Fate and Transport (Models)	,
PCB Concentrations in Water	
PCB Concentrations in Sediment	
PCB Concentrations in Fish	.363150 (w.n.)
Field Studies	505150 (w.p.)
Biota	
Animal Studies (ecological)	
Fish Population	810 (3.2.2)
Fish Concentration Trend Analysis	619 (3.2.2)
PCB Concentrations in Fish	212627 (w.n.)
	312027 (w.p.)
Fish Consumption	
Human Health Risk Assessment (HHRA)	
Ecological Risk Assessment (ERA)-analysis	
Support of Dredging	
Risk Benefit	553 (7.1)
Fish Habitat	(- () () ()
Benthic Habitat	` '
Flood	422186 (10.1)
Sediment Transport Model	
Erosion	
PCB Release	364582 (6.1), 407426 (w.p.)
Fort Edward	
PCB Discharge	
Hudson Falls	
Remnant Deposits	617 (2.1)
GE's Model	
HUDTOX	
FISHRAND	
Peer Review	843 (6.4.3)
Sub-Reach Scale	,
Remedial Alternatives	847 (6.1.2)
Habitat Replacement	` '
Dredging	
Submerged Aquatic Vegetation (SAV)	
Historic Sites	
Hot Spot	,
Habitat	
Havitat	

Submerged Aquatic Vegetation (SAV) Fish Habitat	593 (4.5)
HUDTOX	
Non Cohesive Sediment	
Cohesive Sediment	833 (2.4.1)
Sediment Transport Model	
Erosion	363193 (2.4)
Human Health Risk Assessment (HHRA)	
Fish Consumption	
Institutional Controls	710 (0.1.0)
Fishing	` '
Connelly Study	
PCB Concentrations in Fish	549 (7.1)
PCB Exposure	7.67 (O.1.1)
PCB Concentrations in Water	567 (3.1.4)
PCB Toxicity	
Animal Studies (toxicity)	262704 () 541 (2.1.1.2)
Weight-of-Evidence	* * * * * * * * * * * * * * * * * * * *
	571 (3.1.1.1)
Sediment Removal	313280 (4.2)
Hydraulic Dredging	262500 (10.1)
Mechanical Dredging	· · · · · · · · · · · · · · · · · · ·
Legal Issues	
ADAD-	423426 (1.2), 424247 (1.2.1)
ARARs	
Disposal	
Dungasing and Tunnafan Facility	424926 (1.2.1)
Processing and Transfer Facility	424913 (1.2.1)
Lighting	
Adverse Impacts	358825 (8 3 2)
Biota	330023 (0.3.2)
Animal Studies (ecological)	
Dredging	805 (8 3 3)
Dredging	
Adverse Impacts	645 (8.3.1)
Long Term Effectiveness and Permanence	
Institutional Controls	359565 (11.6)
Long Term Monitoring	· · ·
Long Term Trends	
Mathematical Model	
PCB Concentrations in Fish	
Bounding Calculation	609 (6.4.2)
Low Resolution Coring Report (LRCR)	` '
J 1 \ /	

PCB Burial	
Data Evaluation and Interpretation	
Report (DEIR)	
Bed Stability (Instability)	577 (2.2)
PCB Concentrations in Sediment	
Fate and Transport	
PCB Burial	607 (6.4.3)
Lower Hudson	
Fate and Transport (Models)	, , , , , , , , , , , , , , , , , , , ,
PCB Concentrations in Fish	
FISHRAND	313699 (w.p.)
PCB Concentrations in Water	(1 /
PCB Concentrations in Fish	
PCB Transport to Lower	
Hudson River	313787 (2.4.3)
Preliminary Remedial Goal (PRG)	,
Recovery Time	313765 (1.1)
Risk Benefit	
Remedial Alternatives	
Natural Resource	799 (6.3)
Superfund (NPL) site	
Mass Removal of PCBs	* *
Mass-Per-Unit-Area (MPA)	
PCB Concentrations in Sediment	597 (4.3)
Mathematical Model	,
Recovery Time	589 (6.4)
Metals	
Dioxins and Furans	407876 (6.1.3)
Disposal	• •
Monitored Natural Attenuation	
Monitoring Program	253427 (10.2)
Monitoring Program	255 .27 (10.2)
PCB Concentrations in Fish	
Long Term Monitoring	
Field Studies	313297 (3.3)
Resuspension	
Drinking Water Supply	362637 (9.2)
More Harm Than Good	502037 (5.2)
Long Term Effectiveness and Permanence	
Short Term Risks and Impacts	485 (11.5)
National Academy of Sciences (NAS)	
Record of Decision (2001 ROD)	
Natural Attenuation	
Biodegradation	313261 (7.2)
PCB Concentrations in Fish	
1 CD Concentrations in Fish	

		(2.0 (2.6)
	Ecological Risk Assessment (ERA)-analysis	3.629 (2.6)
	PCB Concentrations in Sediment	
	PCB Mass	
	Sedimentation	.633 (2.6)
	PCB Toxicity	, ,
	Dechlorination	639 (2.3)
	Source Control	.037 (2.3)
	Recovery Time	
	Risk Benefit	.405926 (11.4)
Naviga	ation	
	Canal System	.705 (8.1)
	Downtime	
	Navigational Dredging	
		757 (0.5)
NT X	Dredging	
	York State	.459 (2)
No Ac		
	Effectiveness of Implementability Cost	.313970 (10.2)
Noise		
	Adverse Impacts	
	Dredging	767 (8.2)
	Dredging	., (0.2)
	0 0	250100 (0.2)
	Adverse Impacts	
	Environmental Impact Study (EIS)	
	Regulatory Analysis	.699 (8.2)
Non C	ohesive Sediment	
	PCB Concentrations in Sediment	
	PCB Inventory	
	Backfill	313266 (4.2.2)
Odor	Dackiii	.313200 (4.2.2)
Ouoi	N . ID	
	Natural Resource	
	Air Quality Impacts	_
Oppos	ition to Dredging	.313388 (1.3)
PCB B	Burial	
	PCB Concentrations in Sediment	
	Sedimentation	
	Thompson Island Pool (TIP)	619 (2.1)
DCD C	Concentrations in Fish	.017 (2.1)
РСВС		
	Assumptions	
	PCB Transport to Lower Hudson River	
	Source Control	.823 (6.1)
	Remedial Goals (Fish)	
	Preliminary Remedial Goal (PRG)	.547 (7.1)
PCR C	Concentrations in Sediment	. (/
LODC	PCB Burial	
	Low Resolution Coring Report (LRCR)	
	Inday 7	

PCB Loss	641 (2.2)
Tri+ PCBs	424694 (w.p.)
PCB Concentrations in Water	
Natural Attenuation	631 (2.6)
PCB Concentrations in Fish	• •
Natural Attenuation	635 (2.6)
PCB Concentrations in Sediment	255353 (w.p.)
PCB Inventory	_
PCB Loss	(1 /
Sediment Sampling	
Thompson Island Pool (TIP)	
PCB Inventory	625 (2.2)
PCB Mass	028 (2.2)
PCB Inventory	369451 (4.2)
PCB Source	307 131 (1.2)
Flood	
HUDTOX	821 (6.1.1)
Historic Sites	` ,
Hudson Falls	313444 (2.1)
Source Control	
	572 (2.1)
Remnant Deposits	
HUDTOX	` /
PCB Transport to Lower Hudson River	835 (6.1.1)
PCB Release	(10 (0.1)
Phase 1	643 (2.1)
PCB Toxicity	
Animal Studies (toxicity)	250201 (2.2.1)
Biota	359281 (3.2.1)
Human Health Risk Assessment (HHRA)	
Animal Studies (toxicity)	
Weight-of-Evidence	
PCB Transport to Lower Hudson River	337780 (11.4)
Peer Review	
Scientific Method	467 (1.3.1)
Preliminary Remediation Goal (PRG)	
Biota	
PCB Concentrations in Fish	313300 (3.3)
PCB Transport to Lower Hudson River	
Ecological Risk Assessment (ERA)-analy	sis
Lower Hudson	831 (7.1)
Remedial Alternatives	362555 (3.3)
Remedial Goals (Fish)	551 (7.1), 561 (7.1)
FDA Standard	. , , , , , , , , , , , , , , , , , , ,
Human Health Risk	
Assessment (HHRA)	545 (3.3)
Inday 9	` '

Processing and Transfer Facility	313704 (5.1.2)
Legal Issues	,
ARARs	487 (11.6) 313749 (1.3)
Treatment	
Adverse Impacts	` '
Production Rates	233210 (w.p.)
Downtime	(71 /10 1)
Schedule	6/1 (10.1)
Project Size	-04 (44.9)
Remedial Alternatives	, ,
Public Participation	
	471 (1.3)
Community Acceptance	427 (1.3), 437 (1.3), 441 (1.3)
Processing and Transfer Facility	313728 (1.3), 431 (1.3)
Railroad	
Record of Decision (1984 ROD)	\ 1 /
Legal Issues	377 (1.3)
Recovery Time	
Adaptive Management	422647 (9.4)
FISHRAND	122017 (7.1)
PCB Concentrations in Fish	
	770 (2.4.2)
Bioaccumulation	//9 (2.4.2)
Regulatory Analysis	107 (1.1)
Freshwater Ecosystem	497 (1.1)
Odor	
Legal Issues	
Reliability	366358 (5.1.3)
Remedial Action Objective (RAO)	
Remediation Goals (Fish)	
Schedule	
FDA Tolerance Level	853 (4.1)
Risk Benefit	` '
Remedial Alternatives	
Remedy Selection	
Cost Effective	595 (4.4)
Short Term Risks and Impacts	
Long Term Effectiveness and Permanence.	313723 (1.1)
Surface Concentration	313723 (1.1)
Mass-Per-Unit-Area (MPA)	500 (4.2.2)
Sediment Texture	599 (4.2.3)
Remediation Goals (Fish)	(- 1)
Fish Consumption	559 (7.1)
Legal Issues	
FDA Tolerance Level	375 (1.1)
Remedial Sequence	669 (10.1)
Index-9	

Remedy Selection	
HUDTOX	
Bounding Calculation	
PCB Concentrations in Fish	451 (6)
Monitored Natural Attenuation	
No Action	337854 (11.1)
Remedial Alternatives	
Source Control	` '
Residual Concentrations	(5.12)
Backfill	
PCB Concentrations in Sediment	312663 (w n)
Capping	312003 (w.p.)
PCB Source	
HUDTOX	837 (6.1.3)
Resuspension	` '
Resuspension	
Biota	330740 (w.p.)
Submerged Aquatic Vegetation (SAV)	902 (0.2)
Dredging	803 (9.2)
HUDTOX	262207 (6.1.4)
Fish Concentration Trend Analysis	363207 (6.1.4)
PCB Transport to Lower Hudson River	42.4077 (10.2)
PCB Release	` /
Uncertainty Factors (UFs)	407907 (6.1.4)
Water Quality	
PCB Burial	` '
RI/FS (Reassessment RI/FS)	313799 (2.7)
Risk Benefit	
Capping	
Ecological Risk Assessment (ERA)-analys	sis 364780 (7.2)
Dredging	
PCB Concentrations in Fish	797 (7.1)
Human Health Risk Assessment (HHRA)	
Remedial Alternatives	841 (7.1)
Source Control	
More Harm Than Good	
Fish Consumption	565 (7.1)
Schedule	
Production Rates	253090 (w.p.)
Scientific Method	, <u>,</u>
Phase 2	
Data Evaluation and Interpretation	
Report (DEIR)	627 (2.7)
Sediment Removal	
Sediment Sampling	
1 0	(-· - /

HUDTOX	
FISHRAND	
PCB Concentrations in Sediment	605 (4.2)
Remedial Alternatives	
Confirmation Sampling	313391 (4.2)
Residual Concentrations	
Confirmation Sampling	
Monitoring Program	,
Shoreline Stabilization	655 (10.4)
Short Term Risks and Impacts	
Ecological Risk Assessment (ERA)-analysis	
Dredging	
Long Term Effectiveness and	
Permanence	337860 (11.1)
Habitat	
Biota	
Dredging	807 (9.1)
Socioeconomic Impacts	
	499 (8.5.2), 689 (8.5.2), 691 (8.5.2)
Railroad	
Transportation	312982 (8.1.1)
Source Control	
Monitored Natural Attenuation	405888 (5.3)
PCB Concentrations in Fish	
Uncertainty Factors (UFs)	
Ecological Risk	
Assessment (ERA)-analysis	
Submerged Aquatic Vegetation (SAV)	
Habitat	509 (9.1), 537 (9.1)
Biota	507 (9.1)
	(o -
Habitat Replacement	· · · ·
Monitoring Program	523 (9.3)
Sub-Reach Scale	
Residual Concentrations	
Ecological Risk	
Assessment (ERA)-analysis	
Fate and Transport (Models)	787 (6.1.2)
Support of Dredging	
Fishing	
PCB Exposure	422786 (8.5.3)
Resources	
Fish Population	
Habitat	801 (3.2)
Index-11	

Thompson Island Pool (TIP) PCB Source	
PCB Concentrations in Water	(21 (2.1)
PCB Release	621 (2.1)
PCB Release	
PCB Fingerprinting	
Traffic-Vehicular/Truck	253245 (w.p.)
Socioeconomic Impacts	
Transportation	
Treatment	` /
Hydraulic Dredging	423609 (8.7.2)
Processing and Transfer Facility	
Water Quality	364871 (8.7.2)
Thermal Treatment	
Sediment Stabilization	313758 (5.1.2)
Turbidity Barrier	,
Dredging Technology	667 (10.3)
Unilateral Administrative Order (UAO)	* '
US Fish and Wildlife Service (USFWS)	,
Field Studies	
Biota	253462 (3.2.2)
Volatilization	* *
Air Quality Impacts	, , ,
Human Health Risk Assessment (HHRA)	
Regulatory Analysis	253202 (w.p.)
Water Quality	<u>-</u>
ARARs	495 (1.1)
Dredging	
Downstream Transport	735 (9.2)
Metals	
Wetlands	` * '
Biota	
Habitat Replacement	
Habitat	527 (9.3)
Threatened and Endangered (T&E) Species	
US Fish and Wildlife Service (USFWS)	3595/15 (9.1)
Ob Fish and whalle betylee (ObF Wb)	